Construction and Demolition Waste Best Management Practice in Europe

Galvez Martos, Jose Luis ; Styles, David; Schoenberger, Harald; Zeschmar-Lahl, Barbara

Resources, Conservation and Recycling

DOI:

[10.1016/j.resconrec.2018.04.016](https://doi.org/10.1016/j.resconrec.2018.04.016)

Published: 01/09/2018

Peer reviewed version

[Cyswllt i'r cyhoeddiad / Link to publication](#)

Dyfyniad o'r fersiwn a gyhoeddwyd / Citation for published version (APA):

Galvez Martos, J. L., Styles, D., Schoenberger, H., & Zeschmar-Lahl, B. (2018). Construction and Demolition Waste Best Management Practice in Europe. *Resources, Conservation and Recycling*, 136, 166-178. <https://doi.org/10.1016/j.resconrec.2018.04.016>

Hawliau Cyffredinol / General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal ?

Take down policy

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Construction and Demolition Waste Best Management Practice in Europe

José-Luis Gálvez-Martos^{1,*}, David Styles^{2,3}, Harald Schoenberger⁴, Barbara Zeschmar-Lahl⁵

¹ Systems Analysis Unit, Instituto IMDEA Energía, Móstoles, Madrid, Spain

² School of Environment, Natural Resources and Geography, Bangor University, Bangor, United Kingdom

³Plant and Agri-biosciences Centre, Ryan Institute, NUI Galway, Galway, Ireland

⁴ Universitaet Stuttgart, Institut für Siedlungswasserbau, Wasserguete- und Abfallwirtschaft, Stuttgart, Germany

⁵ BZL Kommunikation und Projektsteuerung GmbH, Oyten, Germany

*Corresponding author. E-mail: joseluis.galvez@imdea.org

Abstract

Construction and demolition waste constitutes a large fraction of all the waste generated in Europe. Its specific impact can be considered rather low, but the large generated volume and embodied resource makes this waste stream an important focus of current European policies. The European Commission has proposed new targets and goals for this waste stream in the Circular Economy package, but, given the rather heterogeneous landscape of waste management practice across Member States, new approaches that take into account the entire value chain of the construction sector are urgently required. This paper synthesises core principles and linked best practices for the management of construction and demolition waste across the entire construction value chain. Systematic implementation of these best practices could dramatically improve resource efficiency and reduce environmental impact by: reducing waste generation, minimising transport impacts, maximising re-use and recycling by improving the quality of secondary materials and optimising the environmental performance of treatment methods.

Keywords

Construction and demolition waste, circular economy, recycling, re-use, best practices, environmental management, waste management, waste logistics, recycled aggregates, plasterboard

Abbreviations

BaU	Business-as-usual
BEMP	Best Environmental Management Practice
CEN	<i>Comité Européen de Normalisation</i>
CO ₂ e	Equivalent CO ₂ emissions
CDW	Construction and Demolition Waste
EMAS	Eco-Management and Audit Scheme
EN	European Norm (European Standards)
PCBs	Polychlorinated Biphenyls
RA	Recycled Aggregates
RCA	Recycled Concrete Aggregates
SWMP	Site waste management plans
WRAP	Waste and Resources Action Programme

37 1. Introduction

38 Currently, the European construction sector produces 820 million tonnes (megagram, Mg, or 1,000 kg) of
39 construction and demolition waste (CDW) every year, which is around 46% of the total amount of total waste
40 generated according to Eurostat (Eurostat, 2017). The average composition of CDW shows that up to 85% of the
41 waste is concrete, ceramics and masonry, although CDW can be heterogeneous depending on the origin, and may
42 contain large amounts of wood and plasterboard (Monier et al., 2011; U.S. Environmental Protection Agency, 1998).
43 In any case, CDW inorganic fraction is frequently characterised as “inert” due to lack of chemical reactivity at
44 ambient conditions. Most CDW consists of excavated materials, which are considered to have a low environmental
45 impact upon disposal. If excavated materials are excluded, around 300 million Mg of CDW were generated in 2014
46 at European construction sites (i.e. EU 28 new construction, demolition or refurbishment activities).

47 Construction and demolition waste is characterised by its high volume and weight but with probably the lowest
48 environmental burden and the highest inert fraction per Mg of all waste streams. Although the specific environmental
49 impact (per Mg) is low if compared with other waste streams, the associated environmental impacts of such a high
50 amount of CDW is an important concern, mostly derived from its logistics and land occupation. Hence, the
51 management of CDW constitutes a priority for most environmental programmes around the world, especially in
52 Europe. In fact, the European Commission (European Commission, 2015a) has proposed that, by 2020, “the preparing
53 for re-use, recycling and backfilling of non-hazardous construction and demolition waste *excluding naturally*
54 *occurring material* defined in category 17 05 04” – i.e. soil (including excavated soil from contaminated sites) and
55 stones not containing dangerous substances – “in the list of waste shall be increased to a minimum of 70% by weight”.
56 Remarkably, the definition excludes naturally occurring materials but introduces overall recovery targets, while some
57 experts have recommended to introduce separate targets per fraction and to revise the definition of treatment
58 operations, as backfilling (Arm et al., 2014; BioIS, 2016). There is also some concern on the use of weight
59 percentages, since waste managers may focus on the dense mineral fractions rather than on other fractions with
60 potentially higher potential environmental impact (Arm et al., 2014).

61 Novel solutions, instruments and approaches are required for the management of CDW. While a recycling rate of
62 70% for non-hazardous construction and demolition waste can be considered an ambitious target in certain countries,
63 the industry has noticed that national circumstances are heterogeneous across European Member States and that such
64 a target lacks incentive for the industry of those countries or regions where recycling rates already exceed 70%
65 (Craven, 2015).

66 Against this background, the clear definition and sharing of best practice techniques is an essential approach in the
67 development of new policy and strategic frameworks for the construction sector, contributing towards the
68 implementation of sustainable development strategy (European Commission, 2015b). This approach underpins the
69 sectoral reference documents developed under article 46 of the Eco-Management and Audit Scheme, EMAS,
70 regulation (European Parliament and the Council, 2009). These sectoral reference documents include a description
71 of best environmental management practices, BEMPs, underpinned by quantitative benchmarks of excellence, based
72 on sector-specific key performance indicators, that validate high levels of environmental performance. Multi-expert-
73 stakeholder involvement in the process of BEMP definition ensures that BEMPs target those areas with proven

improvement potential and economic feasibility. The compilation of priority BEMPs for CDW prevention and management contained in the sectoral reference document for the construction sector therefore establishes a systematic framework to operationalise the circular economy paradigm for important resource flows.

This paper synthesises the main principles underpinning the definition of *best* practices for the management of CDW, reducing waste generation, minimising transport impacts, maximising re-use and recycling by improving the quality of secondary materials, optimising the environmental performance of treatment methods. The authors of this paper draw upon BEMP definition experience and insight gleaned from the development of six sectoral reference documents, and from European stakeholder inputs regarding CDW management for two relevant sectors: the building and construction sector (Joint Research Centre - European Commission, 2012) and the waste management sector (Zeschmar-Lahl et al., 2016).

2. Characteristics of Construction and Demolition Waste (CDW)

CDW is a generic term that defines the waste generated by the economic activities involving the construction, maintenance, demolition and deconstruction of buildings and civil works. The term “site” is, usually, the most appropriate to define a production facility where CDW is generated. Actually, the distributed nature of construction and demolition *sites* is commonly characteristic of the sector in all Member States of the European Union.

The composition of CDW varies widely as a function of the type of site: e.g. road construction generates a huge amount of excavated materials that, if no further use is possible, will become waste, while a building demolition site will generate a large amount of waste concrete. The heterogeneity of construction activities therefore makes impossible to establish reliable consumption patterns of construction materials or waste generation rates per capita, per work or per m² floor area. In this regard, several authors have tried to establish quantitative ranges of CDW generation rates in a benchmarking exercise (Mália et al., 2013). These rates link the construction activity and the amount of waste per unit of built, demolished or refurbished area to CDW indicators for different types of structures, construction techniques and traditional practices. For instance, precast and prefabricated structures generate less construction waste, as the manufacturing process is less wasteful and designs are specific for each building. At the same time, the expected amount of CDW and its composition is substantially different if timber or reinforced concrete structures are used. Table 1 provides an overview of the range of components of CDW. Construction of new buildings generate from 18 to 33 kg per m² built area of waste concrete when using concrete structures, while timber-based structures generate ten times less waste. However, demolition of residential buildings can generate up to 840 kg of waste concrete per demolished m², while timber-based structures generate up to 300 kg per m². In general, concrete is the main material in CDW, if excavated materials are excluded, and is categorised under code 17 01 01 in the European List of Waste (European Commission, 2000). Other important CDW waste codes are 17 01 02 bricks, 17 01 03 tiles, 17 02 01 timber, 17 02 02 glass, 17 02 03 plastics, 17 03 02 bituminous mixtures, 17 04 07 metal mixtures, 17 06 04 insulation materials, 17 08 02 gypsum-based construction materials and 17 09 03 construction and demolition wastes (including mixed wastes) containing hazardous substances.

Table 1. Construction and Demolition Waste composition (BioIS, 2016)

Although the specific environmental impact (per Mg) is low if compared with other waste streams, the aggregate environmental impacts of the large quantities of CDW are significant, and derive mostly from logistics and land occupation at the waste end of the value chain (and resource consumption upstream). The impact of CDW logistics and treatments is shown in Table 2. The most relevant environmental aspects of CDW generation are influenced by design decisions at the start of the construction value chain; ‘designing-out’ waste is a term in use for CDW, and refers to design and planning commercially available techniques to avoid the generation of waste. The most popular designing out waste technique is the use of prefabricated modules, which is more common in modern methods of construction. With this approach, more than 80% of total construction waste can be avoided. For instance, the construction of a new residential building where the structure is prefabricated would save around 80 to 100 kg of waste per 100 m² floor area (Mália et al., 2013).

Table 2. Life cycle environmental burdens for one Mg of Construction and Demolition Waste treated according to different methods (Blengini and Garbarino, 2010)

Some European countries already achieved the objective of 70% recycling for CDW. Statistics show that the total mass flow of recovered waste accounts for more than 80% of the total waste generation in Member States as the Netherlands, Germany or Denmark (Eurostat, 2017). However, in some regions there is a significant amount of illegal dumping and a heterogeneous market for secondary materials, which hinders the development of secondary materials market, that may not be reflected in official statistics. For instance, high collection rates of well-segregated CDW are achieved in Spain but the market uptake of recycled materials is really low; large storage areas at treatment plants have essentially become temporary landfills (Joint Research Centre - European Commission, 2012).

Indeed, an inherent problem of CDW management at national level is the compilation of reliable statistics to inform and monitor policy. The mineral fraction of construction waste constitutes category 12.1 of the European Regulation on waste management statistics, which basically differs from the categories defined in the European list of waste. Therefore, the success of certain policies at national level are not easy to monitor. Figure 1 shows CDW treatments that Member States reported in the year 2014 (Eurostat, 2017). As observed, a huge amount of waste is basically sent to final disposal, mainly landfill.

Figure 1. Construction and Demolition Waste’s Mineral fraction treatment in 2014 (Eurostat, 2017)

Depending on the nature of the construction project, concrete waste ranges 40 to 85% of the total waste generated on site (Rimoldi, 2010). Except for some elements such as beams or blocks, which can be *dismantled* from a building, “clean” crushed concrete waste is barely re-usable and its recycling produces an usually downgraded product (aggregates), as recovery of initial constituents from cement or the original aggregate is not feasible. Recycled concrete aggregates, RCA, are usable for the so-called unbound applications (e.g. road sub-base fillings) or as secondary materials in the manufacture of new concrete. Europe consumes around 2.6 billion Mg of aggregates (European Aggregates Association, 2017). If the entire quantity of CDW is transformed into recycled aggregates, only a 2% substitution of virgin aggregates would be achieved. In the UK, 6.4% of the aggregates for concrete came from secondary sources or recycled materials in 2015 (The Concrete Centre, 2016). Therefore, there are no technical barriers for a virtual 100% recycling of the main constituents of CDW, concrete and ceramic wastes, but barriers derived from their commercialisation, the market of virgin materials or their logistics. A good example of these barriers are observed in Spain, where, during 2017, 100 million Mg of aggregates were consumed in 2017 (ANEFA,

2017), but it is thought to correspond to an actual 22% of the total production capacity of the sector. On the other hand, only 10 million Mg of CDW are generated, from which the current management system can generate up to 3 million Mg of usable recycled aggregate (FERCD, 2015); the impact of this secondary material in the total system would only be 3% of the total aggregates market, but competing with the highly available resource of natural aggregates.

The highest quality use of RCA is for new concrete. However, the low cost of extracted natural aggregates is a main drawback for the uptake of secondary materials in many locations in Europe, as extracted resources would have similar costs to recycled aggregates. As shown for the case of Spain, in some Member States there is a healthy market of affordable natural aggregates so the economic savings on the total cost of aggregates in the final product are insignificant. In addition, the environmental impact of natural and recycled aggregates e.g. in terms of greenhouse gases emissions is highly dependent on their transport (Blengini and Garbarino, 2010). Recycled aggregates from masonry and ceramic wastes, usually mixed with waste concrete, are less usable in bound applications, but their volume is certainly smaller and their technical viability is proven (Jiménez et al., 2013).

Several case studies around Europe demonstrated more than 95% CDW recycling, where recycling means any recovery operation by which waste materials are reprocessed into products materials or substances, as defined in the Waste Framework Directive (2008/98/EC) (Joint Research Centre - European Commission, 2012) and showed how market barriers could be overcome in relation to (i) availability, (ii) economics and (iii) acceptability. The profit margin on recycled aggregates depends on the localisation of the resource, which has to be closer than conventional quarries, and the respective taxes applied to landfill and natural aggregate extraction (European Aggregates Association, 2006). Denmark and the Netherlands have been very successful in promoting the recycling of CDW using these kind of instruments. Along with other drivers, these market-oriented regulatory tools, including taxes or levies, developed by the public administration, or environmental credits certified by relevant industry-led ecolabeling schemes such as BREEAM or LEED, contribute to improved outcomes.

Finally, a cultural misunderstanding is that recycled aggregates in concrete have much lower operational performance than natural aggregates (Adams et al., 2016). Researchers have shown that, with proper waste separation, recycled concrete aggregates can substitute 100% natural aggregates in quality applications of concrete (Adams et al., 2016; McGinnis et al., 2017; Silva et al., 2014; Wijayasundara et al., 2017).

3. Best Environmental Management Practices for Construction and Demolition Waste

3.1. Methodology for the identification of Best Environmental Management Practices

According to the EMAS regulation 1221/2009, a BEMP is the “most effective way to implement the environmental management system by organisations in a relevant sector and that can result in best environmental performance under given economic and technical conditions”. The identification of BEMPs is a process very similar to that for best available techniques within the framework of the European Directive on Industrial Emissions, formerly Integrated Pollution Prevention and Control (Schoenberger, 2009). In a first approach, data is collected from the literature, industrial experience, and direct data and feedback from a technical working group of European experts. Performance data is used to recognise best environmental management practices, while a deeper study is required to qualify the selection of best practices regarding applicability and economic efficiency. In the case of the construction sector, a

186 technical working group of European experts, practitioners, regulators, constructors, developers, etc was established
187 at the beginning of the exercise. In a first meeting, the experts give recommendations and indications to the team of
188 the Joint Research Centre of the European Commission. The received information drives research on the topic, helps
189 organising site visits and experts are consulted. A first draft report is delivered to the technical working group, which
190 then ratifies, modify or comment on the list of best practices, the indicators used to measure their performance and
191 benchmarks of excellence where applicable.

192 The approach for the identification of BEMPs is further defined in other publications derived from EMAS sectoral
193 reference documents, e.g. for energy efficiency (Galvez-Martos et al., 2013), supply chain management (Styles et al.,
194 2012) in the retail trade sector, or water management in the hospitality sector (Styles et al., 2015).

195 3.2. *List of best practices*

196 Table 3 summarises BEMPs selected for the management of CDW. Best practice definition involved consideration
197 of the entire value chain of the construction sector, and follow a sequence along the chain. In the first instance, best
198 practices address the definition of management strategies in a preconstruction phase (project inception and design),
199 then techniques around prevention and collection are proposed in a second category, and re-use, treatment and
200 material recovery practices are discussed in the third and fourth category.

201 **Table 3. Summary of best environmental management practices for CDW**

202 Figure 2 illustrates the integration of the identified best environmental management practices into the construction
203 value chain, i.e. preconstruction (inception and design), construction, demolition and waste to products.

204 **Figure 2. Best environmental management practices for CDW management in the construction value chain**

205 CDW best practices essentially operationalise circular economy principles within the construction and demolition
206 sector and beyond. Most of the defined best practices in e.g. demolition are oriented to maximise the re-use of
207 elements, facilitate recycling, material recovery and secondary uses of materials through e.g. quality assurance
208 schemes for materials derived from waste.

209 This work presents those best practices with proven environmental benefits that are replicable and affordable for
210 waste authorities and managers. Single case studies have generally been avoided where they do not have wider
211 applicability, and some best practices are specifically oriented to drive significant environmental improvement in
212 countries and regions with a poor performance of CDW management – these BEMPs may be considered “average”
213 or “standard” in the context of other national frameworks outside of their intended target.

214 3.3. *Waste management strategies*

215 The elaboration of **CDW management plans or strategies** is a very common approach in Europe, since the
216 elaboration of integrated waste management plans is mandatory (European Parliament and the Council, 2008).
217 However, the quality of implementation and consequent outcomes diverge considerably; for instance, CDW
218 management has become a privately driven activity in countries with a restricted supply of virgin materials, well-
219 extended environmental awareness and with a reliable CDW recycling infrastructure. In general, to be effective,
220 CDW management plans must be accompanied by regulation and enforcement practices, or economic drivers, such
221 as taxes, levies, etc. Key elements of a best practice strategic plan at different scales are summarised in Table 4.

222 **Table 4. Common elements of a best practice strategic plan at national, regional and local (municipal or county) scale**

223 The impact of CDW management strategies is not easily quantifiable for two main reasons: the evolving economic
224 framework introduces difficulty in the quantification of business as usual, BaU, performance; and the allocation of
225 the environmental benefits between the whole strategy or to a single technique or management practice (e.g. the
226 establishment of a levy or the investment in recycling plants).

227 In any case, there are examples where a whole strategy resulted in a rapid improvement from the BaU counterfactual
228 scenario: in the UK, the establishment of sound environmental policies and strategies around CDW through the Waste
229 Resources Action Programme, WRAP, contributed to the increase of the recycling rate up to 90% for the whole UK
230 (DEFRA, 2017), achieving exemplar cases with 100% concrete or metal wastes from construction sites diverted from
231 landfill, and achieving savings of more than 200 kg CO₂ per GBP 100,000 value of the construction (Institute of
232 Carbon and Energy, 2017). In the UK, the involvement of stakeholders was articulated using the “Halving Waste to
233 Landfill Commitment”, which involved more than 750 companies from the whole supply chain of construction
234 (Waste and Resources Action Programme, 2011).

235 One of the key aspects for strategic plans is the involvement of stakeholders. The International Solid Waste
236 Association established in 2012 a range of good practice mechanisms in the always challenging involvement of
237 stakeholders (ISWA, 2012):

- 238 • Consultation, communication and involvement of users.
- 239 • Participatory and inclusive planning: those parties showing interest should meet regularly to measure the
240 performance of the system, define or update objectives and monitor progress against benchmarks.
- 241 • Inclusivity at all levels: the creation of local waste platforms with decision-making attributions is a
242 particularly recommended practice.

243 As for any environmental policies, effective waste management strategies include a mix of complementary measures
244 such as regulatory, economic, educational and informative instruments (OECD, 2013; van Beukering et al., 2009).
245 In this context, **economic instruments** are designed to motivate waste producers to divert waste from landfills,
246 recycle more waste and optimise the use of resources, so waste is (i) prevented, (ii) well managed, and (iii) optimally
247 treated. These instruments can have greater impact than regulatory mechanisms, and introduce taxes or levies to the
248 polluter, linking the cost of waste treatment with the actual amount of waste generated by, for example, charging per
249 unit of waste. While these instruments have more recently been implemented for household waste streams, the
250 construction industry and CDW managers have extensive experience on these types of instrument, including landfill
251 taxes, aggregate levies or others. With regard to best practice, the business to business, B2B, schemes in Europe are
252 particularly remarkable. For instance, the existence of a B2B deposit refund scheme is sometimes a common practice
253 for highly re-usable packaging, like pallets, construction packaging, drums and others (Lundesjo, 2011; Waste and
254 Resources Action Programme, 2008a), and these practices have dramatically reduced the amount of waste generated
255 at construction sites. Although waste managers are not involved in this particular approach, they are key in the
256 management of the necessary reverse logistics, e.g. in construction consolidation centres.

257 At the local level, some municipalities have applied **traceability** requirements for CDW in their local licensing. For
258 example, municipalities in Spain are charging a deposit on the estimated amount of wastes reported in the site waste
259 management plan as part of the essential licensing requirement. The deposit is re-paid to the contractor when “waste

management certificates” are submitted to the authority. This particular deposit-refund scheme, managed by municipalities, has potential to become a BEMP, but its current implementation does not meet BEMP requirements for the following reasons:

- It is oriented to avoid illegal dumping, i.e. it does not increase the performance of the system but avoids a particular local problem of CDW management.
- Legally, municipalities do not need to issue permits for their own construction sites. The waste management deposit becomes, then, voluntary for contractors working with the municipality.
- The lack of enforcement affects the performance of the scheme. While large construction companies and contractors were already applying BEMP without the need for the deposit, small producers are still failing to fulfil this practice.

During the construction activity, **site waste management plans, SWMP**, have been proven as an effective measure for the actors involved in a construction or demolition site to improve the performance of CDW management. The elaboration of SWMPs is a legal requirement in some European countries, but not in all, and therefore may still be considered a BEMP. Best practice SWMP go beyond legal requirements by fitting into an overall ambitious strategy, where two main phases are identified (Joint Research Centre - European Commission, 2012):

- **SWMP design.** In this phase, the scope of the plan is developed, by e.g. identifying materials to be recovered, re-used, recycled and disposed during construction or demolition. Waste management responsibilities are defined, and the instruments for monitoring, collecting and promoting correct waste management practices are identified, along with measurable indicators and targets. During the plan design phase, waste types will be defined, estimated, and the waste management technologies will be sized. A first cost estimation will be produced and potential savings will be identified. Procedures for removal, separation, storage, transportation and any waste handling will be developed. A communication strategy should also be defined in a best practice SWMP. During this phase, waste prevention techniques, re-use and recycling opportunities will be identified per waste stream and their potential on-site application will be evaluated.
- **SWMP implementation.** Once the main procedures and strategies are defined, the waste manager responsible for the site should communicate and explain the plan to all the relevant actors within the site and external stakeholders affected by the site activity. The areas for waste storage and the available resources should be well identified within the site, and waste containers should be placed as close as possible to the generation point. Training and promotion of the plan should be regularly performed, especially with new contractors or subcontractors, and a documentation file shall be kept updated.

3.4. *Prevention and collection*

In the building life cycle, wastes are generated from demolition material (of the previous construction on site), damage of materials, off-cuts, design changes, temporary works materials, contamination of clean materials, packaging, etc. Excavated materials and soils may be considered also as wastes if they are polluted or if for administrative reasons they need to be managed as wastes. Approximately 33% of waste generation on a typical construction site can be attributed to designers failing to implement waste prevention measures during the design phase (Osmani et al., 2008), while the remainder can be considered unavoidable with current practices and

techniques. Table 5 shows some opportunities for *waste prevention during design*, i.e. **designing out waste** (adapted from Waste and Resources Action Programme, 2012).

Table 5. Waste prevention opportunities in the design phase

Modern methods of construction have a huge impact on waste generation during construction, since off-cuts and concrete handling are avoided. The waste reduction potential is up to 90% for techniques such as:

- Volumetric building systems: Off-site manufacturing of three-dimensional modules, e.g. roof and external insulation, roof tiling, brick and block work, etc.
- Substitution of concrete frame: timber.
- Pre-cast panels: panelised building systems for staircases, roofing, basements, etc.
- Steel frames: substitutes concrete and eliminates waste generation.
- Structural insulated panels and prefabricated roof systems.
- Composite panels.
- Pre-cast cladding.
- Light steel frame for building façades.
- Structural pre-cast elements.
- Insulating concrete formwork.

An example of the application of modern methods of construction is the Middlehaven Hotel in the UK (Waste and Resources Action Programme, 2008b), where a series of precast elements, volumetric pods, pre-cast columns and foundations were able to avoid 75% of the total waste expected from traditional construction methods, saving more than half a million EUR from waste disposal and unnecessary construction materials. However, the environmental performance of a specific application should use LCA to evaluate the actual environmental performance.

On-site **waste prevention and collection** are techniques that should have been identified, designed and scoped in a general construction site management protocol, which may be articulated in a specific SWMP. From the endless list of waste management options at construction and demolition sites, four main activities of the waste management activity are identified:

- **Estimation of waste generation and provision of resources.** Best segregation options for a construction site should be analysed in advance of the construction activity, so resources can be allocated for waste management. The estimation of wastes generated during the construction activity should be based on a tailor-made estimation (Martínez-Bertrand and Tomé, 2009), which should be optimised with the help of the previous experience of the contractor.
- **Collection and segregation techniques.** Several collection techniques are needed to help site labourers to perform correctly. Identified standard practices have the following common basis: (i) waste collection bins are identified for each type of waste; the size of each bin or container is appropriate taking into account the estimated amount to be generated, the number of containers and the foreseen number of waste deliveries; (ii) waste collection bins are usually placed at the same point of the site (e.g. labelled as ‘ecopoint’, ‘recycling point’, etc.); (iii) temporary collection points are usually placed next to a work position in order to increase the efficiency of waste segregation, but which usually depends on the characteristics of the position; (iv)

hazardous wastes are collected in a separated point, protected from wind, rain and over a sealed surface with the appropriate measures to prevent and minimise pollution of rainfall water; (v) all labourers, independently if they come from the main contractor or a subcontractor are aware of the on-site waste management techniques, (vi) there is enough space available for waste deliveries by truck; and (vii) waste collection points are identified in a site plan and the plan is made available to all relevant actors.

- **Procedures and methodologies to ensure best management options.** These techniques usually refer to on-site control techniques, such as visual inspection, computerised or photographic register, signs, symbols and information, issuing and control of waste management certificates, and, in case it is required, pre-treatment of waste is available on-site when high segregation rates need to be achieved, e.g. compactors, roll packers, cardboard balers, shredders for wood, or portable crushers.
- **Provision of waste logistics.** Usually, two on-site collection methods are observed: reactive and scheduled. For large fractions, such as inert fractions of CDW, a reactive collection is required, e.g. a full skip is substituted by another empty skip on demand. For smaller volumes of wastes of constant generation, such as those similar to municipal solid wastes, scheduled collection is the best option.

Best management practices on **material use** refer to logistics schemes that optimise material use by minimising the amount of raw materials stored on site, which reduces the likelihood for supplied materials to become waste. In traditional logistics, the majority of materials are stocked when they arrive on a construction site. This means that materials are double handled, increasing the risk of damage and the rate of waste generation along with the subsequent cost. In this sense, *stockholding* is a term defined as the process of holding materials in readiness for subsequent activities (Constructing Excellence, 2006). Material use efficiency can avoid environmental impacts because: less fuel is consumed if less material is transported, less materials leftovers are produced if stockholding is reduced down to a minimum, etc.

Figure 3 shows an overview of logistics techniques at construction sites. Whenever supply is made by manufacturers (e.g. for specially designed construction elements or products), by local or regional suppliers, by urban consolidation centres or by the same construction company, three main practices are observed: *ancillary storage*, *secure storage* and *just-in-time delivery*. Ancillary storage (e.g. for bricks, blocks, timber, etc) is used to buffer the supply of materials for the smooth operation of sites. Secure storage has a similar function, but a higher degree of security has to be ensured for materials of high value (metals, kitchens, sanitary ware, etc.). The third technique is just-in-time delivery and constitutes the preferred technique for the supply of ready-mix concrete and other bulky materials. In the case of construction sites in the centre of large cities, storage typically has to be kept to a minimum due to lack of space. In these cases, delivery is normally just-in-time, while buffering is performed through consolidation centres for best performance.

Figure 3. Supply logistics options to construction sites. Source: (Joint Research Centre - European Commission, 2012)

3.5. *Re-use of materials*

From the circular economy point of view, the best re-use option in the construction sector is the re-use of the entire building. Factors such as space, integrity, aesthetics, refurbishment costs and client satisfaction play a key role on the feasibility assessment of the potential of building re-use (Institute of Civil Engineers, 2008). In many cases, the most economic option will be the demolition of buildings, which, as traditionally conceived, produces large amounts

372 of demolition waste that often results in a significant portion of the total waste stream. **Selective building**
373 **deconstruction** is an alternative to demolition that involves a systematic disassembly with the objective of
374 maximising re-use, recycling and diversion from landfill.

375 Although selective deconstruction is able to separate different types of materials at source, it is not a preferred practice
376 due to the poor economics of dismantling; the actual effort, if measured in time, skills and labour, is significantly
377 higher than for conventional demolition (Joint Research Centre - European Commission, 2012). Those achieving
378 best performances tend to strategies between conventional demolishing and full component-by-component
379 dismantling. The application of selective deconstruction techniques usually involves the following steps:

- 380 • First, a hazardous substances audit and an evaluation of the need for specialised stripping, e.g. of
381 asbestos, should be performed.
- 382 • Second, manual dismantling of re-usable parts is the preferred option for directly re-usable parts, as glass,
383 precious wood, sanitary ware, heating boilers, re-usable radiators, etc.
- 384 • Once the building is empty of directly re-usable elements, floor coverings, ceilings and combustible and
385 non-combustible waste should be stripped and segregated.
- 386 • Finally, depending on the type of building, wooden beams, steel frames can be re-used, while buildings
387 with concrete are usually demolished and concrete waste crushed to produce aggregates.

388 This selective dismantling of buildings has several advantages over conventional demolition; it increases the
389 diversion rate of CDW from landfills towards more sustainable direct re-use of building components and recycling
390 of materials. Time and resource allocation are usually the main drawbacks of a deconstruction process. However,
391 adaptive planning of the deconstruction works can also lead to considerable reductions of deconstruction duration.

392 **Re-use**, as a best practice for CDW management, refers to all harvested materials, construction elements and building
393 components that can be used in a specific site, such as:

- 394 • Harvested construction products and building elements, e.g. bricks, tiles, concrete slabs, beams, wood
395 frames, etc.
- 396 • Re-usable auxiliary materials, such as wood from formworks, pallets, auxiliary structures. The re-use of these
397 is a very common practice in the construction sector and has a non-negligible impact on the economic
398 performance of construction contractors.

399 The re-use of building components and construction products has a significant effect on the overall life cycle
400 environmental performance of the construction activity. Approximately 40% of embodied energy can be saved,
401 despite an increase in transportation needs, and more than 60% of the carbon footprint of the concrete structure can
402 be saved when re-using prefabricated slabs (Roth and Eklund, 2003).

403 3.6. *Waste treatment and material recovery*

404 Current **CDW processing and recycling techniques** can be considered well established and their implementation is
405 common across Europe. However, the nature of the final secondary materials and the market penetration differ
406 widely. A common CDW recycling plant usually consists of (1) reception, weighing and visual inspection, (2) manual
407 preselection (for unsegregated streams), rejection and diversion to alternative treatments, (3) screening of large

408 materials, (4) magnetic separation, (5) manual separation of plastic, wood and other waste streams if required, (6)
 409 crushing, and (7) screening and secondary crushing, which is applied depending on the goal product mix.

410 A CDW treatment plant will normally produce aggregates from the inert fraction of CDW, while other types of
 411 wastes or recovered materials (metals, plastic, wood, and MSW-like in some cases) are diverted to the appropriate
 412 treatments. From well sorted waste, high quality aggregates can be produced, since clean crushed concrete aggregates
 413 have a much higher applicability than mixed crushed masonry-concrete aggregates. As an example, the standard
 414 classification of recycled aggregates (RA) in Germany is made through a DIN standard 4226-100 (Table 6).

415 **Table 6. Classification of aggregates according to German DIN 4226-100**

416 The final destination of RA is the substitution of virgin materials. Although main substitution rates are achieved in
 417 low grade applications, as base, or sub-base materials for roads and backfilling, higher grade applications, e.g.
 418 aggregate for new structural and non-structural aggregate, have a high potential. Although some generalisations can
 419 be made, as shown in **Table 7**, caution is always required in the application of standards in the construction industry,
 420 as they are usually applied at national level (Pellegrino and Faleschini, 2016). Upcycling is possible, but applicability
 421 is quite low: e.g. crushed concrete sand can be used in cement production, but with a very low substitution rate of the
 422 raw meals (around 2%) due to composition limitations (Hauer and Klein, 2007).

423 The benefits from CDW recycling as aggregates cannot be generalised without a large number of assumptions.
 424 Studies have considered different scopes and produced varied results owing to different assumptions or framework
 425 conditions. The following conclusions (Hiete, 2013) regarding the environmental performance of crushed concrete
 426 recycling have been made:

- 427 • Site characteristics are critical: the location influences transport distances while composition influences the
 428 nature of recycled materials and determines the final application.
- 429 • During the use phase, there is no fixed standard for the leachability of recycled aggregates.
- 430 • When balancing benefits from primary aggregate substitution, the type of application and the type and origin
 431 of the natural aggregate strongly influences the life cycle performance.
- 432 • However, washing, which is applied when site segregation is poor, can count more than 99% of the total
 433 environmental impact (Korre and Durucan, 2009).
- 434 • Although there are studies confirming the better environmental performance of the recycled aggregates
 435 supply chain, the production and crushing of concrete is more energy intensive than for primary aggregates,
 436 and the environmental impact can be compensated if the ratio of transport distances for primary aggregates
 437 versus recycled aggregates is above four (Chowdhury et al., 2010).

438 **Table 7. Possibilities for recycled construction materials.**

440 The use of RA and RCA helps to reduce the use of virgin materials from quarries, which usually have a high
 441 environmental impact at local level. For example, the German regions of Berlin and Baden-Württemberg achieve
 442 recycling rates higher than 90% for CDW, which can be attributed to the existence of proper standards and
 443 environment regulations (APPRICOD (Assessing the Potential of Plastics Recycling in the Construction and
 444 Demolition Activities), 2006; QRB, 2009). From the life cycle perspective, the use of recycled aggregates produces

445 a net reduction in the CO₂ emissions and primary energy consumption, since the extraction of virgin materials is
446 avoided, but some trade-offs must be taken into account. For instance, regarding the health and safety issue in
447 recycling plants, at least 20 to 25% of dust in the surroundings of recycling plants has been detected to be of a
448 diameter of less than 10 µm (Kummer et al., 2010) and, therefore, its release should be duly controlled, e.g through
449 the implementation of de-dusting devices in screening, crushing and handling operations. Also, the location of
450 recycling plants close to urban areas, although good in terms of life cycle environmental impact, has an adverse effect
451 due to noise, vibration and emissions from the commonly used diesel engines.

452 The recycling of CDW from building construction or demolition introduces the risk of potentially **hazardous**
453 **materials** that are contained in the original waste material. For instance, concrete foundations from the 1960's contain
454 hazardous PCB substances, which are considered to be very harmful, e.g. as carcinogens. Other materials, such as
455 solvents in paints, tar-based emulsions from roads, asbestos, etc., are controlled, although the national approaches
456 differ; a current best practice example of PCB from construction management can be found in Denmark (Butera et
457 al., 2014; Zeschmar-Lahl et al., 2016).

458 In order to achieve a less heterogeneous management landscape on the management of hazardous CDW in Europe,
459 the European Commission mandated CEN for harmonisation on the assessment of dangerous substances. As a
460 response, a new Technical Committee – CEN/TC 351 – was created: ‘Construction products: assessment of release
461 of dangerous substances’. This committee will provide tools and assessment methods for the quantification of
462 dangerous substances, which may be released from construction products to the environment into the soil, ground
463 water, surface water and indoor air (Ilvonen, 2013). In this respect, an important aspect of the hazardous potential of
464 CDW is the leachability of chemicals from produced RA. It is common that RA coming from ashes, slags and other
465 wastes are well regulated regarding their composition, while for recycled concrete some countries apply a set of
466 different criteria. For instance, the Netherlands does not apply a waste regulation to RA, but a common regulation is
467 used for natural or RA in terms of environmental criteria.

468 **Quality assurance schemes** have become a key element for the marketing of secondary materials produced from
469 CDW recycling. The construction industry, in general, has a very conservative approach to innovation, which is
470 basically due to its traditional behaviour and the legal liability of architects, engineers, developers and contractors
471 regarding their final products (Zeschmar-Lahl et al., 2016), so construction stakeholders rely on sound standards to
472 support advances. On the other hand, RAs have usually had a low- grade application, e.g. as backfilling material for
473 quarries, some sub-base applications for road and cover for landfills. But, it is well known that certain qualities of
474 RA or RCA fit higher grade applications, e.g. as aggregate material in concrete for structural and non-structural
475 applications. A quality assurance scheme, in this context, would establish common rules for producers and, very
476 importantly, would increase the confidence of final users. A best practice quality assurance scheme is one that drives
477 increased uptake of RAs and RCAs, following a voluntary agreement approach, rather than regulation, including all
478 stakeholders along the construction value chain. Among many measures, it should include waste segregation and
479 diversion from landfill, while defining environment-related criteria, e.g. as leaching characteristics and reference
480 standards, and awarding, if possible, an End-of-Waste or by-product character to the secondary material produced.
481 For instance, based on well-defined protocols and procedures, the region of Baden-Württemberg in Germany
482 classifies three quality levels for RAs based on their leaching characteristics, and defines suitable applications for

each classification (QRB, 2009). Delgado et al., 2009, collected information from some frontrunner quality assurance schemes in Europe, such as the Austrian construction materials recycling association, the region of Flanders, the SFS standard 5884 in Finland, or the programme Aggregain in the UK, established by WRAP. Although it is out of the scope of this paper to discuss the suitability of environmental performance standards, the lack of harmonisation in Europe regarding RA is remarkable and problematic. It was noted that current requirements in many Member States of the European Union are less restrictive for virgin materials than for those secondary materials consisting on RA (Saveyn et al., 2014). Regarding the performance of RA, the most important standard is the European EN 12620 under approval (CEN (European Committee for Standardization), 2013), which specifies the properties of aggregates regardless of the origin. This standard is an attempt to standardise, under the current construction products regulation (European Parliament and the Council, 2011) a harmonised set of quality requirements. Other standards are applicable for roads (EN 13242) or asphalts (EN 13043).

A key exemplary case of the circular economy in action is the **recycling of plasterboard**. Plasterboard (also known as drywall, gypsum board, wallboard, etc.) consists of kiln dried panels made of gypsum plaster (rehydrated calcium sulphate dihydrate) pressed between two thick sheets of paper. In Europe, 2.35 million Mg of waste plasterboard per year from construction and demolition projects are produced and an extra 0.6 million Mg are produced during its manufacturing and installation (Marlet, 2017). However, almost all the waste plasterboard can be successfully fed into the manufacture of new plasterboard or as raw material for other uses, and plasterboard itself can incorporate wastes from other industrial processes, such as calcium sulfate from flue gas desulfurization. Plasterboard produced with 89% recycled material (mainly flue gas desulfurization wastes) was achieved by Knauf in 2013 (Knauf, 2013).

The importance of plasterboard segregation and its impact on the whole CDW reprocessing is of high relevance. A separate thematic area was set up by WRAP in the UK, where several local authorities introduced waste plasterboard collection at their Household Waste Collection centres, e.g. Sheffield (Waste and Resources Action Programme, 2009). Also, at European level, the project GypsumToGypsum (Marlet, 2017) aimed to integrate better the supply chain of gypsum-based products by closing the loop and to increase the quantity of gypsum-based waste being diverted from landfill for recycling. Europe demands around 15 million Mg of plasterboard, and the annual production of its waste is around 2.35 million Mg. So, therefore, there is more than enough capacity for recycling.

From the whole value chain of the construction sector, several best practices have an impact on plasterboard products:

- Plasterboard panels are subject of designing-out waste practices, since proper sizing and just-in-time practices would reduce the amount of wasted plasterboard considerably.
- Plasterboard is a durable product, so panels and tiles made of plasterboard, with no damage, can easily be reinstalled (re-used).
- The product itself can incorporate secondary material up to virtually 100% of the raw material, although the industry tends to use natural gypsum. E.g. in Germany the demand for the construction material gypsum is mainly fulfilled (currently at least 60%) by gypsum as a side product of the flue gas desulphurization in the electricity production process at coal power plants.
- Reprocessing waste plasterboard can produce gypsum of high quality, according to certain standards, with a variety of potential uses apart from new plasterboard: raw material for cement manufacture, roads sub-base, and soil improvement for agriculture. The characteristics of each secondary product are defined in quality

assurance schemes e.g. for the UK. In general, the presence of fibres in the waste limits its applicability to a 25% of the total raw meal for new plasterboard.

- Waste plasterboard segregation benefits other CDW recycling, as sulphates, generally coming from plasterboard, are mixed with other CDW fractions in unsorted waste management, which prevents the application of the recycled aggregate.

3.7. *Applicability, economics, and achievable environmental benefit*

During the research activity, all the BEMPs on CDW management have been qualified in terms of achievable environmental benefits, conditions for applicability, costs and economics of implementation, operational data, reference organisations in Europe and cross-media effects (Joint Research Centre - European Commission, 2012; Zeschmar-Lahl et al., 2016). Table 8 summarises the most important information regarding the applicability, economics and environmental performance for each of the best practice described in the previous sections.

Table 8. Applicability, economics and achievable environmental benefits of the best environmental management practice for construction and demolition waste

4. Final remarks

Observations made during the exercise showed clearly an obvious heterogeneity among European Member States, especially in two areas: treatment of waste and development of markets for secondary materials. It is obvious that the technology and the potential for high performing waste management systems is already in the market and available to those regions, municipalities, waste authorities or waste contractors willing to improve their performance. However, the construction sector shows a traditional behaviour, which heavily relies on standards, while being completely economically driven. In addition, the high variety of actors involved in the CDW value chain creates a complex mesh of responsibilities, with very different decision-making chains across European Member States. Of course, the low impact of any waste-related decisions on construction project budgets does not encourage improvement beyond current standard practices. Therefore, most of the observed efforts focus on the creation of drivers addressing the whole landscape of construction stakeholders across the construction value chain. Systematic documentation of current best practices observed across Europe provides an evidence base to develop policies and management strategies that deliver circular economy solutions to the construction sector.

5. References

- Adams, M.P., Fu, T., Cabrera, A.G., Morales, M., Ideker, J.H., Isgor, O.B., 2016. Cracking susceptibility of concrete made with coarse recycled concrete aggregates. *Construction and Building Materials* 102, 802–810. <https://doi.org/10.1016/j.conbuildmat.2015.11.022>
- ANEFA, 2017. Actualidad del Sector [WWW Document]. URL <http://www.aridos.org/wp-content/uploads/2018/01/ANEFActualidad51.pdf.pdf> (accessed 4.3.18).
- APPRICOD (Assessing the Potential of Plastics Recycling in the Construction and Demolition Activities), 2006. Towards Sustainable Plastic Construction and Demolition Waste Management in Europe. [WWW Document]. URL <http://www.acrplus.org/index.php/en/project-themes/previous-projects/2-content/277-appricod> and <http://www.acrplus.org/images/pdf/document142.pdf> (accessed 10.2.17).
- Arm, M., Wik, O., Engelsén, C.J., Erlandsson, M., Sundqvist, J.-O., Oberender, A., Hjelmar, O., Wahlström, M., 2014. ENCORT-CDW - Evaluation of the European recovery target for construction and demolition waste. Nordisk Ministerråd. <https://doi.org/10.6027/NA2014-916>

560 BioIS, 2016. Resource Efficient Use of Mixed Wastes: Improving management of construction and demolition waste
561 [WWW Document]. URL <http://ec.europa.eu/environment/waste/studies/pdf/construction/Minutes.pdf>
562 (accessed 11.14.17).

563 Blengini, G.A., Garbarino, E., 2010. Resources and waste management in Turin (Italy): the role of recycled
564 aggregates in the sustainable supply mix. *Journal of Cleaner Production* 18, 1021–1030.
565 <https://doi.org/10.1016/j.jclepro.2010.01.027>

566 Butera, S., Christensen, T.H., Astrup, T.F., 2014. Composition and leaching of construction and demolition waste:
567 Inorganic elements and organic compounds. *Journal of Hazardous Materials* 276, 302–311.
568 <https://doi.org/10.1016/j.jhazmat.2014.05.033>

569 CEN (European Committee for Standardization), 2013. Aggregates for concrete (under Approval) [WWW
570 Document]. URL <https://standards.cen.eu> (accessed 11.15.17).

571 Chowdhury, R., Apul, D., Fry, T., 2010. A life cycle based environmental impacts assessment of construction
572 materials used in road construction. *Resources, Conservation and Recycling* 54, 250–255.
573 <https://doi.org/10.1016/j.resconrec.2009.08.007>

574 Constructing Excellence, 2006. Supply chain integration, logistics and e-trading. Stockholding. [WWW Document].
575 URL http://constructingexcellence.org.uk/wp-content/uploads/2015/05/denne_stockholding.pdf (accessed
576 12.18.17).

577 Craven, P., 2015. Are Current EU C&D Waste Recycling Targets an Obstacle to Growth? [WWW Document]. URL
578 <https://waste-management-world.com/a/are-current-eu-cd-waste-recycling-targets-an-obstacle-to-growth>
579 (accessed 10.3.17).

580 DEFRA, 2017. Digest of Waste and Resource Statistics [WWW Document]. URL
581 [https://www.gov.uk/government/uploads/system/uploads/attachment_data/file/607416/Digest_of_Waste_a
582 nd_Resource_Statistics__2017_rev.pdf](https://www.gov.uk/government/uploads/system/uploads/attachment_data/file/607416/Digest_of_Waste_and_Resource_Statistics__2017_rev.pdf) (accessed 12.18.17).

583 European Aggregates Association, 2017. European Aggregates Association: A sustainable industry for a sustainable
584 Europe. Annual Review 2015-2016.

585 European Aggregates Association, 2006. Aggregates from Construction and Demolition Waste in Europe [WWW
586 Document]. URL http://www.uepg.eu/uploads/Modules/Publications/pub-12_en-plaquette.pdf (accessed
587 11.15.17).

588 European Commission, 2015a. Proposal for a directive of the European Parliament and of the Council amending
589 Directive 2008/98/EC on waste (No. COM/2015/0585).

590 European Commission, 2015b. Sustainable Development - Environment - European Commission [WWW
591 Document]. URL <http://ec.europa.eu/environment/eussd/> (accessed 11.15.17).

592 European Commission, 2000. COMMISSION DECISION of 3 May 2000 replacing Decision 94/3/EC establishing a
593 list of wastes pursuant to Article 1(a) of Council Directive 75/442/EEC on waste and Council Decision
594 94/904/EC establishing a list of hazardous waste pursuant to Article 1(4) of Council Directive 91/689/EEC
595 on hazardous waste.

596 European Parliament and the Council, 2011. Regulation (EU) No 305/2011 of the European Parliament and of the
597 Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products and
598 repealing Council Directive 89/106/EEC Text with EEA relevance [WWW Document].

599 European Parliament and the Council, 2009. REGULATION (EC) No 1221/2009 OF THE EUROPEAN
600 PARLIAMENT AND OF THE COUNCIL of 25 November 2009 on the voluntary participation by
601 organisations in a Community eco-management and audit scheme (EMAS), repealing Regulation (EC)
602 No 761/2001 and Commission Decisions 2001/681/EC and 2006/193/EC. Official Journal of the European
603 Union L342/1.

604 European Parliament and the Council, 2008. Directive 2008/98/EC of the European Parliament and of the Council of
605 19 November 2008 on waste and repealing certain Directives.

606 Eurostat, 2017. Generation of waste by waste category, hazardousness and NACE Rev 2 activity.

607 FERCD, 2015. Report on Production and Management of Construction and Demolition Waste in Spain (2009-2013)
608 (In Spanish).

609 Galvez-Martos, J.-L., Styles, D., Schoenberger, H., 2013. Identified best environmental management practices to
610 improve the energy performance of the retail trade sector in Europe. *Energy Policy* 63, 982–994.
611 <https://doi.org/10.1016/j.enpol.2013.08.061>

612 Hauer, B., Klein, H., 2007. Recycling of Concrete Crusher Sand in Cement Clinker Production. Presented at the
613 International Conference on Sustainability in the Cement and Concrete Industry, Lillehammer, Norway.

614 Hiete, M., 2013. 4 - Waste management plants and technology for recycling construction and demolition (C&D)
615 waste: state-of-the-art and future challenges, in: Pacheco-Torgal, F., Tam, V.W.Y., Labrincha, J.A., Ding,
616 Y., Brito, J. de (Eds.), *Handbook of Recycled Concrete and Demolition Waste*, Woodhead Publishing Series

in Civil and Structural Engineering. Woodhead Publishing, pp. 53–75.
<https://doi.org/10.1533/9780857096906.1.53>

Ilvonen, O., 2013. Assessing release of hazardous substances from construction products – Review of 10 years of experience with a horizontal approach in the European Union. *Building and Environment* 69, 194–205.
<https://doi.org/10.1016/j.buildenv.2013.08.010>

Institute of Carbon and Energy, 2017. Embodied Energy and Embodied Carbon [WWW Document]. Circular Ecology. URL <http://www.circularecology.com/embodied-energy-and-carbon-footprint-database.html> (accessed 12.18.17).

Institute of Civil Engineers, 2008. The Demolition Protocol [WWW Document]. URL <https://www.2degreesnetwork.com/groups/2degrees-community/resources/demolition-protocol-2008/> (accessed 12.19.17).

ISWA, 2012. Solid waste: guidelines for succesful planning [WWW Document]. URL https://www.pseau.org/outils/ouvrages/abrelpe_iswa_solid_waste_guidelines_for_successful_planning_2012.pdf (accessed 12.18.17).

Jiménez, J.R., Ayuso, J., López, M., Fernández, J.M., de Brito, J., 2013. Use of fine recycled aggregates from ceramic waste in masonry mortar manufacturing. *Construction and Building Materials, Special Section on Recycling Wastes for Use as Construction Materials* 40, 679–690. <https://doi.org/10.1016/j.conbuildmat.2012.11.036>

Joint Research Centre - European Commission, 2012. Best Environmental Management Practice in the Building and Construction sector. Final Draft. [WWW Document]. URL ec.europa.eu

Knauf, 2013. Knauf Sustainability Report 2013 [WWW Document]. URL knauf.co.uk (accessed 11.12.17).

Korre, A., Durucan, S., 2009. Life Cycle Assessment of Aggregates [WWW Document]. URL <http://ceramics.org/wp-content/uploads/2017/05/EVA025-MIRO-Life-Cycle-Assessment-of-Aggregates-final-report.pdf> (accessed 12.19.17).

Kummer, V., van der Pütten, N., Schneble, H., Wagner, R., Winkels, H., 2010. Ermittlung des PM10-Anteils an den Gesamtstaubemissionen von Bauschuttaufbereitungsanlagen. *Gefahrstoffe – Reinhaltung der Luft* 11–12, 478–482.

Lundesjo, G., 2011. Pallet waste and reusable pallets at Aggregate Industries [WWW Document]. URL http://www.wrap.org.uk/sites/files/wrap/AI_pallet_study.pdf (accessed 12.18.17).

Mália, M., de Brito, J., Pinheiro, M.D., Bravo, M., 2013. Construction and demolition waste indicators. *Waste Management & Research* 31, 241–255.

Marlet, C., 2017. GtoG - from gypsum to gypsum: a circular economy for the gypsum industry with the demolition and recycling industries - Life 11 ENV/BE/001392.

Martínez-Bertrand, C., Tomé, M., 2009. Gestión de residuos de construcción y demolición (RCDS): importancia de la recogida para optimizar su posterior valorización, in: *Congreso Nacional Del Medio Ambiente (España)*.

McGinnis, M.J., Davis, M., de la Rosa, A., Weldon, B.D., Kurama, Y.C., 2017. Strength and stiffness of concrete with recycled concrete aggregates. *Construction and Building Materials* 154, 258–269.
<https://doi.org/10.1016/j.conbuildmat.2017.07.015>

Monier, V., Mudgal, S., Hestin, M., Trarieux, M., Mimid, S., 2011. Management of construction and demolition waste [WWW Document]. URL http://ec.europa.eu/environment/waste/pdf/2011_CDW_Report.pdf (accessed 11.14.17).

OECD, 2013. The OECD database on instruments used for environmental policy and natural resources management [WWW Document]. URL <https://www.oecd.org/env/tools-evaluation/env%20policy-natural%20resources%20brochure.pdf> (accessed 12.18.17).

Osmani, M., Glass, J., Price, A.D.F., 2008. Architects' perspectives on construction waste reduction by design. *Waste Management* 28, 1147–1158. <https://doi.org/10.1016/j.wasman.2007.05.011>

Pellegrino, C., Faleschini, F., 2016. Sustainability Improvements in the Concrete Industry, Green energy and technologies. Springer.

QRB, 2009. Qualitätssicherungssystem Recycling-Baustoffe, Baden-Württemberg [WWW Document]. URL www.qrb-bw.de (accessed 10.1.17).

Rimoldi, A., 2010. The Concrete Case. Workshop on the Management of C&D waste in the EU [WWW Document]. URL http://ec.europa.eu/environment/waste/construction_demolition.htm

Roth, L., Eklund, M., 2003. Environmental evaluation of reuse of by-products as road construction materials in Sweden. *Waste Management* 23, 107–116. [https://doi.org/10.1016/S0956-053X\(02\)00052-1](https://doi.org/10.1016/S0956-053X(02)00052-1)

Saveyn, H., Eder, P., Garbarino, E., Muchova, L., Hjelmar, O., van der Sloot, H., Comans, R., van Zomeren, A., Hyks, J., Oberender, A., 2014. Study on methodological aspects regarding limit values for pollutants in aggregates in the context of the possible development of end-of-waste criteria under the EU Waste Framework Directive. JRC Technical Report. EUR 26769.

674 Schoenberger, H., 2009. Integrated pollution prevention and control in large industrial installations on the basis of
675 best available techniques – The Sevilla Process. *Journal of Cleaner Production* 17, 1526–1529.
676 <https://doi.org/10.1016/j.jclepro.2009.06.002>

677 Silva, R.V., de Brito, J., Dhir, R.K., 2014. Properties and composition of recycled aggregates from construction and
678 demolition waste suitable for concrete production. *Construction and Building Materials* 65, 201–217.
679 <https://doi.org/10.1016/j.conbuildmat.2014.04.117>

680 Styles, D., Schoenberger, H., Galvez-Martos, J.L., 2015. Water management in the European hospitality sector: Best
681 practice, performance benchmarks and improvement potential. *Tourism Management* 46, 187–202.
682 <https://doi.org/10.1016/j.tourman.2014.07.005>

683 Styles, D., Schoenberger, H., Galvez-Martos, J.-L., 2012. Environmental improvement of product supply chains:
684 Proposed best practice techniques, quantitative indicators and benchmarks of excellence for retailers. *Journal*
685 *of Environmental Management* 110, 135–150. <https://doi.org/10.1016/j.jenvman.2012.05.021>

686 The Concrete Centre, 2016. Concrete Industry Sustainability Performance Report. 9th report:2015 performance data
687 [WWW Document]. URL [https://www.concretecentre.com/Publications-Software/Publications/The-Ninth-](https://www.concretecentre.com/Publications-Software/Publications/The-Ninth-Concrete-Industry-Sustainability-Perform.aspx)
688 [Concrete-Industry-Sustainability-Perform.aspx](https://www.concretecentre.com/Publications-Software/Publications/The-Ninth-Concrete-Industry-Sustainability-Perform.aspx) (accessed 11.15.17).

689 U.S. Environmental Protection Agency, 1998. Characterization of building-related construction and demolition
690 debris in the United States [WWW Document]. URL [https://www.epa.gov/sites/production/files/2016-](https://www.epa.gov/sites/production/files/2016-03/documents/charact_bulding_related_cd.pdf)
691 [03/documents/charact_bulding_related_cd.pdf](https://www.epa.gov/sites/production/files/2016-03/documents/charact_bulding_related_cd.pdf) (accessed 11.14.17).

692 van Beukering, P.J.H., Bartelings, H., Linderhof, V.G.M., Oosterhuis, F.H., 2009. Effectiveness of unit-based pricing
693 of waste in the Netherlands: Applying a general equilibrium model. *Waste Management* 29, 2892–2901.
694 <https://doi.org/10.1016/j.wasman.2009.07.002>

695 Waste and Resources Action Programme, 2012. Achieving effective Waste Minimisation. Guidance for construction
696 clients, design teams and contractors [WWW Document]. URL
697 <http://www.wrap.org.uk/sites/files/wrap/Waste%20min%20mid%20level%20FINAL1.pdf> (accessed
698 12.1.17).

699 Waste and Resources Action Programme, 2011. The Construction Commitments: Halving Waste to Landfill.
700 Signatory Report 2011 [WWW Document]. URL [wrap.org.uk](http://www.wrap.org.uk) (accessed 12.1.17).

701 Waste and Resources Action Programme, 2009. Implementing a waste plasterboard collection scheme at Sheffield
702 City Council HWRC. Plasterboard case study. [WWW Document]. URL [wrap.org.uk](http://www.wrap.org.uk) (accessed 11.12.17).

703 Waste and Resources Action Programme, 2008a. Reusable packaging in construction The benefits of reusable
704 packaging options for construction product suppliers [WWW Document]. URL
705 <http://www.wrap.org.uk/sites/files/wrap/RTP%20briefing%20note%20for%20suppliers%20-%20Final.pdf>
706 (accessed 12.18.17).

707 Waste and Resources Action Programme, 2008b. Middlehaven Hotel Construction [WWW Document]. URL
708 http://bioregional.com.au/wp-content/uploads/2015/05/WRAPMiddlehavenHotelConstruction_Mar08.pdf
709 (accessed 12.18.17).

710 Wijayasundara, M., Mendis, P., Crawford, R.H., 2017. Methodology for the integrated assessment on the use of
711 recycled concrete aggregate replacing natural aggregate in structural concrete. *Journal of Cleaner Production*
712 166, 321–334. <https://doi.org/10.1016/j.jclepro.2017.08.001>

713 Zeschmar-Lahl, B., Schoenberger, H., Styles, D., Galvez-Martos, J.-L., 2016. Background Report on Best
714 Environmental Management Practice in the Waste Management Sector. Preparatory findings to support the
715 development of an EMAS Sectoral Reference Document. Report for the European Commission’s Joint
716 Research Centre [WWW Document]. URL [http://www.bzl-](http://www.bzl-gmbh.de/de/sites/default/files/WasteManagementBackgroundReport.pdf)
717 [gmbh.de/de/sites/default/files/WasteManagementBackgroundReport.pdf](http://www.bzl-gmbh.de/de/sites/default/files/WasteManagementBackgroundReport.pdf) (accessed 11.15.17).