

## Accurate estimation of fish length in single camera photogrammetry with a fiducial marker

Monkman, Graham G; Hyder, Kieran; Kaiser, Michel J; Vidal, Franck P

## **ICES Journal of Marine Science**

DOI: 10.1093/icesjms/fsz030

Published: 01/11/2020

Peer reviewed version

Cyswllt i'r cyhoeddiad / Link to publication

Dyfyniad o'r fersiwn a gyhoeddwyd / Citation for published version (APA): Monkman, G. G., Hyder, K., Kaiser, M. J., & Vidal, F. P. (2020). Accurate estimation of fish length in single camera photogrammetry with a fiducial marker. *ICES Journal of Marine Science*, 77(6), 2245-2254. https://doi.org/10.1093/icesjms/fsz030

Hawliau Cyffredinol / General rights Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

· Users may download and print one copy of any publication from the public portal for the purpose of private study or research.

- You may not further distribute the material or use it for any profit-making activity or commercial gain
   You may freely distribute the URL identifying the publication in the public portal ?

Take down policy If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

# 1 2

# Accurate estimation of fish length in single camera photogrammetry with a fiducial marker

- 3 Graham G. Monkman <sup>a,\*</sup>, Kieran Hyder <sup>d,e</sup>, Michel J. Kaiser <sup>a,c</sup>, Franck P. Vidal <sup>b</sup>
- <sup>4</sup> <sup>a</sup> School of Ocean Sciences, Bangor University, Menai Bridge, Anglesey LL59 5AB, United
- 5 Kingdom
- <sup>6</sup> <sup>b</sup> School of Computer Science, Bangor University, Menai Bridge, Anglesey LL59 5AB,
- 7 United Kingdom
- <sup>c</sup> Marine Stewardship Council, Marine House, 1 Snow Hill, London EC1A 2DH
- <sup>9</sup> <sup>d</sup> Centre for Environment, Fisheries & Aquaculture Science, Pakefield Road, Lowestoft,
- 10 Suffolk NR33 0HT, United Kingdom
- <sup>11</sup> <sup>e</sup> School of Environmental Sciences, University of East Anglia, Norwich Research Park,
- 12 Norwich, Norfolk NR4 7TJ, United Kingdom. Tel. +44 (0)1502 524501
- 13
- 14 \* Corresponding author at: School of Ocean Sciences, Bangor University, Menai Bridge,
- 15 Anglesey LL59 5AB, United Kingdom. Tel.:+ 44 (0)1248 382842.
- 16 Email addresses: gmonkman@mistymountains.biz (G.G. Monkman); michel.kaiser@msc.org
- 17 (M.J. Kaiser), kieran.hyder@cefas.co.uk (K. Hyder); f.vidal@bangor.ac.uk (F.P. Vidal)
- 18

## 19 **ORCID**

- 20 G.G. Monkman http://orcid.org/0000-0002-5645-1834, K. Hyder http://orcid.org/0000-0003-
- 21 1428-5679, M. J. Kaiser http://orcid.org/0000-0001-8782-3621, F.P. Vidal
- 22 https://orcid.org/0000-0002-2768-4524
- 23
- 24 Keywords fiducial marker, image distortion, OpenCV, photogrammetry, single camera, total
- 25 length estimation

## 26 Abstract

27 Videogrammetry and photogrammetry are increasingly being used in marine science for 28 unsupervised data collection. The camera systems used to collect such data are varied and often 29 complex. In contrast, digital cameras and smartphones are ubiquitous, convenient for the user 30 and an image automatically captures much of the data normally recorded on paper as metadata. 31 The limitations of such an approach are primarily attributed to errors introduced through both 32 the image acquisition process and lens distortion of the collected images. In the present study, 33 a methodology is presented to achieve accurate 2-dimensional (2-D) total length (TL) estimates 34 of fish without specialist camera equipment or proprietary software. Photographs of depressed 35 (flat) and fusiform fish were captured with an action camera using a background fiducial 36 marker, positioned at the distal plane of the subject; a foreground fiducial marker, at the 37 proximal plane of the subject and a laser marker, projected on to the subject's surface. To 38 correct image distortions, the geometric properties of the lens were modelled with OpenCV. 39 The accuracy of TL estimates were corrected for parallax effects using a novel iterative 40 algorithm requiring only the initial length estimate and known morphometric relationships. 41 OpenCV was effective in correcting image distortion, decreasing RMSE by 96% and the 42 percentage mean bias error (%MBE) by 50%. By undistorting the image and correcting for 43 parallax effects a % MBE [95% CIs] of -0.6% [-1.0, -0.3] was achieved and RMSE was reduced by 86% to 2.1%. Estimation of the lens to subject distance using the similar triangles calibration 44 45 method resulted in the best estimation of TL. The present study demonstrates that the 46 morphometric measurement of different species can be accurately estimated without the need 47 for expensive, complex or bulky camera equipment making it particularly suitable for 48 deployment in citizen science and other volunteer based data collection endeavours.

## 49 **1 Introduction**

50 Cost reductions and advances in camera equipment and supporting technologies (e.g. durability, storage and computing capacity, connectivity, and supporting software) are 51 52 stimulating research and development into the applications of photogrammetry and 53 videogrammetry (hereafter referred to as photogrammetry) to marine research (Bicknell, Godley, Sheehan, Votier, & Witt, 2016; Struthers, Danylchuk, Wilson, & Cooke, 2015). 54 55 Potential applications include remote electronic monitoring (virtual observation) of 56 commercial fisheries to assess catch (e.g. White et al., 2006; Chang et al., 2010; Hold et al., 57 2015; Bartholomew et al., 2018) and bycatch (e.g. Bartholomew et al., 2018), ecological 58 studies using fixed cameras (e.g. Bouchet and Meeuwig, 2015; Schmid et al., 2017), direct 59 observational surveys (e.g. Harvey et al., 2001, Jaquet, 2006), behavioural studies (e.g. Nguyen 60 et al., 2014, Claassens and Hodgson, 2018) and in aquaculture (e.g. Costa et al., 2006).

Length data is particularly important in the assessment of fish stocks in recreational and commercial capture fisheries (Pauly & Morgan, 1987) however, the collection of length measurements is time consuming and costly. Photogrammetry can increase throughput (Chang et al., 2010), mitigate against factors such as observer biases (Faunce & Barbeaux, 2011; Harvey et al., 2001), and be more cost-effective per data point acquired than manual at-sea length observations and length sampling (Chang et al., 2010; National Oceanic and Atmospheric Administration, 2015a, 2015b).

The equipment typically deployed for photogrammetry includes multiple parallel lasers (e.g. Deakos, 2010; Rogers *et al.*, 2017; Bartholomew *et al.*, 2018) and/or multiple cameras (e.g. Dunbrack, 2006; Rosen *et al.*, 2013; Neuswanger *et al.*, 2016). In parallel laser systems the lasers create a visible fiducial marker of known length at the surface of the subject of interest. When the plane of the subject surface is aligned with the plane of the camera sensor then the actual length represented by an image pixel will be invariant across the subject provided the image and the subject are not distorted. Under these assumptions an accurate length estimate can be made. Multi-camera systems are mathematically more complex, but allow 3-dimensional subject length (and other measures) to be estimated using triangulation methods (e.g. Neuswanger *et al.*, 2016). Accurate length estimates have also been derived by deployment of a simpler system by analysing images captured with a single camera and a physical fiducial marker of known length (Hold et al., 2015; van Helmond, Chen, & Poos, 2017).

81 Photogrammetry has the potential to widen the participation of non-scientists as novel 82 sources of data. Citizen science projects can use smartphone applications to improve 83 engagement with participants (reviews Hyder et al., 2015, Venturelli et al., 2017) and can be 84 utilised for species identification from images captured using smartphones (Fishbrain, 2018). 85 The assessment of marine recreational fisheries (MRF)-which can be data poor even in 86 developed countries (ICES, 2017)—may particularly benefit from the deployment of simple 87 photogrammetry solutions. Surveys of MRF frequently have a diary phase in which anglers 88 record details of their catch (ICES, 2017). Volunteer based assessments may be the best means 89 of collecting longitudinal data under budgetary limitations.

90 To accurately estimate length from images using a fiducial marker several corrections are 91 necessary. Cameras have different intrinsic tangential distortion, where the sensor plane is not 92 perpendicular to the optical axis. Additionally, the wide-angle lenses-typical of action 93 cameras and smartphones—exhibit radial distortion. These factors introduce systematic length 94 estimation errors as the actual length represented by pixels across the captured image plane 95 varies with the location of the pixel in the image. Any estimation of actual size can be biased 96 by the increasing depth and aspect between the subject, the fiducial marker and the camera 97 (parallax effect). Camera calibration is well understood (see Szeliski, 2010 pp288-295) 98 nonetheless, correcting fiducial marker-made length estimates for subject aspect in single 99 camera systems has received little research attention. Optical corrections can be made using 100 the thin-lens equation provided the lens to subject distance is known. However, measuring the 101 lens to subject distance is impractical for some uses, such as in volunteer based projects where 102 the volunteer could not be expected to accurately measure the lens to subject distance each time 103 an image was captured.

104 This study aims to introduce a methodology to minimise errors in morphometric 105 measurements of fish (and other organisms) when using single camera photogrammetry. The 106 methodology is particularly relevant to the automation of length extractions in machine vision 107 pipelines for volunteer led applications used in the assessment of recreational fisheries or small 108 scale and developing artisanal or commercial fisheries. The objectives are to (i) empirically 109 compare the accuracy of low-cost foreground, background and laser fiducial markers; (ii) 110 validate the effectivity of OpenCV in correcting intrinsic lens distortion in any camera; (iii) 111 describe methods to minimise error in length estimates made with fiducial markers; and (iv) 112 compare the effectiveness of applying a lens distortion correction and parallax correction 113 without prior knowledge of the lens to subject distance.

## 114 **2 Methods**

## 115 2.1 Image acquisition and actual TL measurement

116 Two species of fish with different body shape were selected to support the generalisability 117 of the presented methodology. The European sea bass is a pelagic predator with fusiform body 118 shape (i.e. roughly cylindrical in cross section and tapers towards the ends). Conversely, the 119 common dab is a flat fish with a depressed body shape. Photographs of euthanised European 120 sea bass (*Dicentrarchus labrax*, n = 43) were gathered *in-situ* at two commercial fish processors 121 in North West Wales, UK in November 2016 and March 2017. Images of common dab 122 (*Limanda limanda*, n = 32) were captured at the School of Ocean Sciences laboratory, Bangor 123 University, UK in January 2017. The camera system was a Nextbase 512G camera encased in a custom waterproof housing fitted with a 12v battery. The Nextbase 512G optical system has a wide angled field of view (FoV) and significant barrel distortion, which allowed the effectiveness of lens distortion correction to be evaluated. To provide stability the camera housing was mounted on a Manfrotto 244 variable friction arm and bracket. Projective distortion was minimised by using spirit levels to ensure the principle lens plane and the surface on which the photographic subject lay were parallel.

130 The camera was set to record video at 30 frames per second and a resolution of  $1280 \times 720$ pixels. Video capture—as opposed to single frame photographs—was used to minimise 131 132 perturbation to the camera.. The distance between the surface on which the fish lay and the 133 front of the camera housing was measured with a 1 m steel rule (required for depth adjustment 134 as outlined later). The total length (TL) of the fish (i.e. the distance between the tip of the snout 135 to the tip of the caudal fin) was measured using a fish measuring board with the caudal lobes 136 pushed gently together and then allowed to settle without further coercion. All measuring rules 137 were validated with a rule certified to an accuracy of 0.9998%. Throughout the manuscript, all 138 lengths refer to TL unless otherwise specified.

The precision and accuracy of the three types of fiducial markers were compared (Fig. 1), these were; (i) marker positioned at the backplane (*distal plane*) of the subject (henceforth *background marker*); (ii) paired lasers projected onto the near surface of the subject (henceforth *laser marker*); and (iii) a marker positioned on the fish surface (*proximal plane*) closest to, and parallel with, the plane of the camera lens (henceforth *foreground marker*).

144



Fig. 1. Placement of the three fiducial markers on a European sea bass. The checkerboard cell scale is  $1 \text{ cm}^2$ .

145

The foreground and background markers were a checkerboard of 1 cm<sup>2</sup> cells mounted on a flat polycarbonate sheet (Fig. 1). The laser marker used two parallel-paired lasers (Odiforce, 3-5mW Green Laser Module) mounted inside the camera housing. The distance between the laser markers at the midpoint of the fish depth was recorded manually because the laser lines were not parallel at the scale of interest due to fabrication errors when seating the lasers within the custom camera housing.

Still JPEG images were extracted from the video using VLC media player (VideoLAN, 2018). TL estimates were made from the still images using ImageJ (Schneider et al., 2012) for each of the 3 fiducial markers. The background fiducial marker actual length per pixel (ALPP) was calculated across the total fish length. The pixel length of the fish was measured in the image by the line segment joining the tip of the snout through the centre of the caudal peduncle and the fork to the intersection with the imaginary line between the tips of the caudal fin.

## 158 **2.2** Hierarchy of length correction refinements

The position of each fiducial marker type in relation to the camera is shown in Fig. 2. It is apparent that the estimation of the ALPP is dependent on the distance between the fiducial marker and the camera. The actual length is invariant however, the size of marker image formed on the camera sensor increases as the object to lens distance decreases. Errors in TL estimation 163 arise because of variation in the distance between the fiducial markers and the fish profile.

164 Measurement errors are also caused by image distortion arising from the geometric properties

165 of the camera-lens system (henceforth *intrinsic camera properties*, as commonly known in the

166 field). To obtain accurate TL estimates, these two sources of error need to be corrected.





Fig. 2. Schematic showing the measurement of total fish length, and the relative position of foreground, background and laser fiducial markers to the camera. Width describes the elevation of the fish above the distal plane.

167 **2.3** Correcting for image distortion

To correct for tangential distortion, radial distortion and lens misalignment, the intrinsic 168 169 parameters of the camera at a fixed zoom (focal length) and the lens distortion coefficients need 170 to be calculated (Szeliski, 2010). Multiple images of a regular 2D pattern were captured in 171 different orientations and the intrinsic camera matrix and distortion coefficients calculated 172 using Python 3.5 and OpenCV (OpenCV team, 2018). This camera profile is saved and can 173 then be reused to undistort images taken with the same camera for a given focal length. Supplementary materials A lists the code used for camera profile creation and undistorting 174 175 images.

176 The efficacy of the distortion correction was estimated by photographing a checkerboard

177 pattern and manually marking the vertices both before and after distortion correction. On an

178 image without radial distortion, the vertices of a checkerboard row or column lie on straight 179 line, therefore the x and y coordinates were regressed and the residuals used to calculate the 180 Euclidean distance in pixels of the marked point from the idealised vertex. The root mean 181 squared error (RMSE) was calculated for each horizontal and vertical line of vertices and 1st and 2<sup>nd</sup> order statistical moments calculated across images. RMSE for a given line is given by 182  $RMSE = (\sum_{i=1}^{n} (e_i - o_i)^2 / n)^{1/2}$ . where  $e_i$  is the *i*<sup>th</sup> expected Euclidean distance of the marked 183 point from the idealised vertex (i.e. 0 pixels) and  $o_i$  is the *i*<sup>th</sup> actual Euclidean distance of the 184 185 distorted vertex from the idealised vertex.

Errors arising from positional differences between fish and camera were minimised by ensuring the camera and fish were aligned as previously described and ensuring the subject was placed on the background marker with minimal body distortion. Henceforth TL estimates taken from an undistorted image are known as *undistorted TL*.

## 190 **2.4** Correcting for subject profile

In the case of the laser and foreground markers, the width of a fusiform fish (*w*, Fig. 2) causes an underestimate of the ALPP, therefore TL (*l*, Fig. 2) is also an underestimate. TL estimations made with a foreground marker were corrected using a well-known manipulation of the thin lens equation where a = b(1 - w)/d (Fig. 3).



Fig. 3. Schematic describing the thin-lens model, which relates actual object lengths to image formation at the camera sensor.

195 This correction (henceforth *depth corrected TL*) can be interpreted as having adjusted the 196 ALPP to be the same as if the foreground fiducial marker was positioned at the distal plane. To 197 calculate *depth corrected TL*, the width of the fish is required, which can be estimated from the 198 length, provided the length-width relationship is known (Jeong, Yang, Lee, Kang, & Lee, 2013; 199 Loy, Boglione, Gagliardi, Ferrucci, & Cataudella, 2000; Rohlf & Marcus, 1993; Tulli, 200 Balenovic, Messina, & Tibaldi, 2009). However, depth corrected TL is subject to systematic 201 error because the estimated length used to derive width is itself an underestimate. This 202 underestimate occurs because the ALPP is calculated from the foreground fiducial marker 203 dimensions, which is nearer the camera lens than a significant proportion of the fish body. To 204 address this, TL was corrected iteratively according to the process shown in Fig. 4. This correction is described as *iterative corrected TL*, using the following equation;  $l_{und} + l_{cor}$  where 205 206 *lcor* is the sum of iteratively calculated lengths larger than a minimum threshold (Supplementary 207 materials C).



Fig. 4. Iterative process to improve accuracy of total length (TL) estimates.TL and widths are estimated using the morphometric relationship between the two dimensions.

208 Iterative corrected TL does not account for the varying width profile of the fish between the 209 proximal and distal subject planes. To test this correction methodology, we compared two 210 different body shapes using common dab and European sea bass and calculated the mean width 211 (mm) for each species. Mean widths were measured by bisecting fish through the long axis of 212 the coronal plane. Bisected samples were then photographed against a white background. 213 Images were thresholded (i.e. subject pixels set to white, background pixels set to black), then 214 the standardised mean width  $\hat{w}$  was derived from the mean pixel width across the thresholded images (Fig. 5), according to  $\widehat{w} = (\frac{1}{n} \cdot \sum_{i=1}^{n} w_i) / \max(w_i)$  where *n* is the number of pixel 215 columns and  $w_i$  is the height in pixels of the  $i^{th}$  column. This factor was used to correct the 216 *iterative corrected TL* to derive the *profile corrected TL*  $(l_p)$  according to  $l_p = \widehat{w} \cdot l_{cor} + l_{und}$ . 217 (Supplementary materials B). 218



Fig. 5. Fish were bisected through the coronal plane (a), and the width profile photographed against a white background. The image was then threshholded (b) and the mean pixel width calculated (c).

### 219 **2.5** Estimation of TL when the distance between lens and fish is unknown

220 Length corrections derived from the thin lens equation require prior knowledge of the 221 distance between the lens and fish. This is impractical for applications where experimental 222 control is not possible. Two methods based on the thin lens model can be used to estimate d if 223 a fiducial marker appears in the image. Firstly, d can be estimated if we know some of the camera properties, according to  $d = (f \cdot h \cdot \dot{s})/(\dot{h} \cdot s)$  where f is the focal length, h is the 224 actual size of the fiducial marker,  $\dot{s}$  is the sensor height in pixels,  $\dot{h}$  is the height of the fiducial 225 marker in pixels and s is the actual size of the sensor. Secondly, d can be estimated by taking 226 one (or more) calibration images with a marker of known length, according to d =227  $(h_c \cdot h \cdot f)/(\dot{h_c} \cdot \dot{h})$ , where f is the focal length,  $h_c$  is the actual size of the calibration marker, 228 h is the actual size of the fiducial marker,  $\dot{h}_c$  is the height in pixels of the calibration marker 229 and  $\dot{h}$  is the height of the fiducial marker in pixels. 230

Both methods were used to estimate *d* (Fig. 3) in the calculation of the *profile corrected TL* and are reported as *calibrated profile corrected TL* and *sensor profile corrected TL*. Supplementary materials C lists the core functions used to produce these corrections. In summary, the mean bias error (MBE) is reported for the variables listed in Table 1. Mean bias

error (MBE) is calculated according to  $MBE = 1/n \cdot \sum_{i=1}^{n} \hat{y}_i - y_i$ , where  $\hat{y}_i$  is the *i*<sup>th</sup> estimate 235

of the *actual TL*  $y_i$ . Percent MBE is given by  $\% MBE = 100/n \cdot \sum_{i=1}^n \hat{y}_i - y_i/y_i$ . 236

Variable	Derived	Comment						
	From							
Actual TL (l)	N/A	TL measured using a fish board						
Distorted TL	Distorted image	TL estimated from an image without any correction for lens distortion						
Undistorted TL	Undistorted image	TL estimated from an undistorted image, reported for all three fiducial marker types.						
Depth corrected TL	Undistorted TL	Adjustment for the difference in the distance between the proximal and distal plane of the subject. Not applicable for the background marker. Uses the actual lens subject distance in the calculation.						
Iterative corrected TL	Depth corrected TL	Apply an adjustment for the initial underestimate of TL.						
Profile corrected TL	Iterative corrected TL	Apply an adjustment accounting for the mean profile width of the subject, i.e. correcting for the parallax effect.						
Calibrated profile corrected TL	Depth corrected TL	Recalculates depth corrected TL using an estimate of the lens to subject distance using similar triangles, then applies the same process used to calculate the profile corrected TL.						
Sensor profile corrected TL	Depth corrected TL	Recalculates the depth corrected TL based on the thin lens equation parameterised with camera properties, then applies the same process used to calculate the profile corrected TL.						

### **Statistical Analysis** 237 2.6

Homogeneity of variance was determined using Levene's test. Where data were 238 239 heterogeneous, estimators of central tendency were calculated using a 1000 sample bias 240 corrected accelerated bootstrap (BCA) in SPSS (IBM Corp, 2011). Note that 95% confidence intervals are quoted in results (in square brackets) unless otherwise stated. 241

A weighted least squares general linear mixed model (wls-GLMM) was used to compare percent errors ( $e_{\%}$ ) for the species (random) and marker (fixed) factors. The vector of weights (*w*) were calculated as follows. Let |r| be the vector of absolute non-standardized residuals from the regression  $e_{\%} \sim species + marker + species * marker$ . Then let *p* be the vector of predicted values of  $|r| \sim species + marker + species * marker$ . Then the vector of weights *w*, is  $w = 1/p^2$ .

## 248 **3 Results**

## 249 **3.1 Size ranges**

European sea bass sizes ranged between 279 mm and 580 mm (Fig. 6a), and common dab between 100 mm to 282 mm (Fig. 6b). For European sea bass, the length-width relationship was taken from data published in Poli et al. (2001) to give *width* =  $0.136 \cdot total \, length -$ 0.367, where length is measured in centimetres. For common dab (n = 21) width =  $0.087 \cdot$ *total length* - 2.915 (R = 0.98, p < 0.001). The standardised mean widths (a proportion) were estimated as 0.598 and 0.505 for European sea bass and common dab respectively.



Fig. 6. Actual total length histograms for European sea bass (a) and common dab (b). N.B. y-axis scales differ.

## 256 **3.2 Distortion correction**

- 257 OpenCV (OpenCV team, 2018) was successful in reducing the radial distortion of the optical
- system of the NextGen 512G camera (Fig. 7). In captured images a pixel represented
- distances of between 0.5 mm and 1.0 mm. The absolute deviation of the vertices from
- idealised straight lines in distorted images was mean  $\pm$  SD 18.2 pixels  $\pm$ 11.3 compared to a
- 261 mean  $\pm$  SD of 0.7 pixels  $\pm$ 0.4 for the undistorted images and RMSE was reduced by 96%
- 262 (distorted RMSE = 21.4 pixels, undistorted RMSE = 0.76 pixels).



Fig. 7.Example image of European sea bass, with radial distortion (a) and without distortion (b). The lines i, ii, iii and iv were set at 10 cm against the background fiducial marker.

## 263 **3.3 Distortion corrected length estimates**

264 The laser and foreground fiducial markers substantially underestimated actual TL in both 265 species without lens correction for laser and foreground markers (Fig. 8; Table 2; aggregated 266 %MBE = -12.9% [-14.1, -11.7]) and this bias was still substantial for laser and foreground 267 markers after distortion correction (Fig. 8; Table 2; *undistorted TL*, aggregated %MBE = -6.5% [-7.1, -5.9]). Estimations made using the background marker were comparatively accurate, 268 269 precise and robust to lens distortion however, TL was slightly overestimated in both species 270 (Fig. 8; Table 2; aggregated %MBE = 2.4% [2.1, 2.7]). Undistorting the images improved 271 background MBE by just 0.6 mm for European sea bass and 0.7 mm for common dab 272 (aggregated % MBE = 2.3% [1.9, 2.7]).In common dab the magnitude of the absolute error [modulus(estimate total length - actual 273

- 274 TL)] increased linearly with fish size for all marker types (Fig. 8b, BCA bootstrap linear

regression, p < 0.05). However, in European sea bass the error increase did not occur when TL estimates were made with the foreground marker (Fig. 8a, BCA bootstrap linear regression, p > 0.05). It is apparent that the systematic linear increase in error was most marked in estimates of common dab TL and with the laser marker (Fig. 8b).



Fig. 8. Error in estimation of total length (tl) for European sea bass (a) and common dab (b) using foreground, background and laser fiducial markers from images without correction of radial and tangential distortion (distorted) and after correcting images for distortion (undistorted). Plot is *actual TL* measured using a fish board *vs*. (corrected total length - *actual TL*). A negative error represents an underestimate of total length. Shaded lines are 95% confidence intervals. Linear regression coefficient (*b*) and R<sup>2</sup> reported. Bootstrapped (n = 1000) confidence intervals are shown as shaded lines. N.B. y-axis scales differ between species.

## 279 **3.4 Length estimate refinements**

```
Applying successive width profile corrections to images substantially improved accuracy for
both species when compared to undistorted TL (Fig. 9) in both species, with an overall
```

reduction in %MBE of 95% (i.e. -12.9% to -0.6%). *Profile corrected TL* had the greatest accuracy and lowest variance (Fig. 9, Table 2) with an aggregated mean %MBE of -0.6% [-1.0, -0.3] and RMSE was reduced by 86% from 14.8% to 2.1%. In both species, *profile corrected TL*, *calibrated profile corrected TL* and *sensor profile corrected TL* suppressed error scaling with increasing TL when compared with non-profile based corrections. This effect is indicated by the reduced magnitude of the linear regression coefficients across the various profile corrections (Fig. 9; ANOVA,  $F_{(1, 28)}$ , = 6.26, p = 0.02,  $\eta^2 = 0.19$ ).



Fig. 9. Error in estimation of total length (tl) for European sea bass (a) and common dab (b), using foreground and laser fiducial markers after correcting images for lens distortion. Plot is *actual TL* measured using a fish board *vs*. (corrected total length - *actual TL*). A negative error represents an underestimate of total length. Linear regression coefficient (*b*) and  $R^2$  reported. Bootstrapped (*n* = 1000) confidence intervals are shown as shaded lines.

	Background			Foreground				Laser					
	n	MBE ± SD	Range	95% CIs	n	MBE ± SD	Range	95% CIs	n	MBE ± SD.	Range	95% CIs	
European sea bass (Dicentrarchus labrax)													
Distorted	43	12.8 ±6.9	-3 - 27	10.9 - 14.7	35	-78.5 ±16.3	-13646	-83.873.5	43	-73.2 ±26.8	-14531	-81.665.2	
Undistorted	43	$13.3 \pm 7.9$	1 - 39	11.1 - 15.6	35	-44.7 ±13.2	-8423	-48.940.5	43	-33.3 ±12.3	-653	-36.929.8	
Depth	-	-	-	-	35	$11.4 \pm 11.7$	-14 - 43	7.6 - 15.4	43	$18.0 \pm 10.0$	4 - 55	15.3 - 21.1	
Iterative.	-	-	-	-	35	$17.5 \pm 12.0$	-3 - 50	13.6 - 21.7	43	$25.8 \pm 13.2$	7 - 69	22.2 - 29.9	
Profile	-	-	-	-	35	$-7.5 \pm 10.9$	-34 - 19	-10.84.2	43	$2.0\pm9.0$	-14 - 31	-0.4 - 4.8	
Sensor profile	-	-	-	-	35	$13.2 \pm 11.3$	-7-41	9.5 - 17.1	43	$20.0 \pm 13.1$	0 - 58	16.6 - 23.6	
Calibration profile	-	-	-	-	35	-6.7 ±10.0	-26 - 18	-9.83.5	43	1.7 ±8.8	-15 - 30	-0.8 - 4.6	
Common dab ( <i>Limanda limanda</i> )													
Distorted	32	3.7 ±2.4	0-9	2.9 - 4.5	32	-12.9 ±9.7	-39 - 0	-16.010.3	28	$-19.3 \pm 14.2$	-522	-24.415.0	
Undistorted	32	$3.0 \pm 2.5$	-3 - 10	2.2 - 3.8	32	-6.8 ±4.8	-21 – 0	-8.55.3	28	$-8.6\pm5.0$	-191	-10.37.1	
Depth	-	-	-	-	32	4.3 ±3.5	-1 - 15	3.2 - 5.4	28	$1.9 \pm 1.9$	-2-6	1.2 - 2.5	
Iterative	-	-	-	-	32	$4.9 \pm 3.9$	-1 - 17	3.8 - 6.1	28	$2.9 \pm 2.6$	-2-9	2.1 - 3.8	
Profile	-	-	-	-	32	-0.8 ±2.6	-9-4	-1.91	28	-2.7 ±1.9	-6-0	-3.42.1	
Sensor profile	-	-	-	-	32	$1.1 \pm 2.5$	-5-8	0.2 - 2.1	28	$0.1 \pm 3.4$	-3 - 13	-1.1 - 1.6	
Calibration profile	-	-	-	-	32	-1.9 ±2.6	-11 - 3	-3.01.0	28	-3.2 ±2.9	-8-4	-4.32.2	

Table 2. Mean bias errors (MBE) ± standard deviation (SD) and 95 % confidence intervals (CIs) for 7 different total length estimates variables calculated using background, foreground and laser fiducial markers from images of European sea bass and common dab. All measurements are given in mm.

291 Of the two profile corrections which used an estimation of subject-lens distance, *calibrated* 292 profile corrected TL had a higher degree of accuracy (calibrated profile corrected TL, %MBE, M = -0.8% [-1.1, -0.4]; sensor profile corrected TL %MBE, M = -2.4% [-1.8, -2.9]) and 293 294 precision (RMSE; calibrated profile corrected TL, 2.1%; sensor profile corrected TL, 3.9%). 295 Profile corrected TL %MBE was reduced in the laser marker when compared to the 296 foreground marker (Fig. 10; mean; laser, -0.18% [-0.6, 0.3]; foreground, -1.1% [-1.6, -0.6]), 297 however, this was not a significant reduction in bias (wls-GLMM, p = 0.76). Error in estimating 298 TL by species was also non-significant (wls-GLMM, p = 0.88).



Fig. 10. Species combined percentage mean bias errors from estimated total length of foreground and laser fiducial markers. Standard deviation represented by error bars.

299

300

## 301 **4 Discussion**

### **302 4.1 Distortion Correction**

303 By applying corrections for geometric lens distortion, the accuracy of length estimates using 304 foreground and parallel laser fiducial markers was significantly reduced in both test fish 305 species. Accuracy was further enhanced by applying increasingly refined corrections to 306 account for the changing distance between the camera and the subject across the surface of the 307 subject. The highest accuracy levels were achieved (%MBE = -0.6 %) when the lens to subject 308 distance was manually measured to mm accuracy, and the TL estimated by iteratively 309 accumulating additional lengths and adding the accumulated sum to the initial length estimate. 310 This level of error is comparable to that observed by Hold et al. (2015) who used a fiducial 311 marker to estimate carapace size in crab and lobster where the mean differences between 312 estimated and actual lengths were 0.1 % and 0.6 % respectively. Similar mean differences have 313 been reported when using paired lasers (Deakos 2010, 0.4 % in Manta alfredi), or multi-camera 314 systems (Rosen et al. 2013 1.0 % in 3 fusiform fish species). The errors observed in length 315 estimates were not significantly different from 0 and equated to 2 mm in 10 cm. Population 316 studies that examine population size-structure typically bin estimates into size classes (Pauly 317 & Morgan, 1987) hence this level of error should not unduly bias biomass catch estimates, size 318 selectivity, or any other size dependent research.

Two approaches were presented to estimate lens to subject distance to correct for parallax errors. Calibration images were shown to be more accurate however, it cannot be assumed this is the general case. The less accurate method calculated lens to subject distance from sensor size in actual units and in pixels. The authors believe the error is likely to have arisen from incorrect manufacturers' figures for actual sensor size and focal length given that actual fiducial marker size, fiducial marker height on the sensor and sensor size in pixels were known 325 precisely. Empirical verification of which method best estimates lens to subject distance could 326 be justified on a per-camera basis and linear modelling of the error should produce a 327 satisfactory correction.

328 Lens distortion correction software is available in multiple packages and the mathematics is well understood for tangential and radial distortion (Szeliski, 2010) however, lens distortion 329 330 correction using OpenCV lens calibration is less well tested. Using this method we reduced 331 RMSE to 0.76 pixels, which equates to submillimetre accuracy at lens to subject distances of 332 between 192 mm and 659 mm. Neuswanger et al. (2016) reported improved correction 333 performance with an extra parameter in the radial distortion model (Szeliski, 2010; Zhang, 334 2000). OpenCV is released under a 3-clause BSD license allowing the code to be modified, reused and redistributed. This makes OpenCV accessible for incorporation into machine vision 335 336 pipelines and across diverse operating systems, including smartphones. Other methods of lens 337 distortion correction tend to be in proprietary software released by the camera manufacturers 338 (e.g. GoPro Studio), in photo editing software (e.g. Adobe Photoshop and PTLens), or in 339 scientific software (e.g. MatLab). VidSync (Neuswanger et al., 2016) is an open source 340 package which supports lens calibration however, it has no API and is authored in Objective 341 C, hence can only be executed on Mac OS. In contrast, OpenCV and Python offer greater 342 platform agnosticism, with support across MS Windows, Mac OS, Android, Linux and other 343 platforms.

Hold *et al.* (2015) found that radial distortion was limited by ensuring the subject was centred in the FoV (also see Rodgers *et al.*, 2017). The parallax effect was empirically controlled with  $a 2^{nd}$  order linear model with FoV as a predictor. This approach was successful in reducing bias however, empirical modelling is unsuitable where the camera model, lens to subject distance and framing of the subject (and fiducial marker) in the image cannot be prescribed. The model will only make known valid predictions over the quadvariate distribution of focal length,

22

subject size, FoV (or lens to subject distance) and the subject rotation over which the model was fitted. Hence combining lens calibration with a mechanistic model of parallax effects (as presented), provides a generalisable solution which should be applicable to a wide range of length estimation correction when using fiducial markers.

In this article, tangential distortion was controlled experimentally. However, where the 354 355 optical axis may not be perpendicular to the subject then tangential distortion must be corrected. 356 OpenCV provides support for calculating the corrective affine transformation and support for 357 identifying checkerboard vertices (or other regular structures). Furthermore, the OpenCV 358 ArUco marker library (Garrido-Jurado, Muñoz-Salinas, Madrid-Cuevas, & Marín-Jiménez, 359 2014) supports marker detection and predicts the affine transformation required to correct tangential distortion based on the orientation of the marker. Hence, further work should be 360 361 undertaken to evaluate the effectiveness of correcting for tangential distortion using the 362 OpenCV API.

363

## 4.2 Fiducial marker type

The foreground fiducial marker had the same accuracy as paired parallel lasers in the 364 estimation of TL. Both markers were subject to the same underlying causes of error because 365 366 the mean ALPP across the marker is not the same as the mean ALPP across the dimension of 367 the subject being measured. The background marker provided accurate estimates of TL, even 368 in radially distorted images. The is because; (i) the ALPP of the marker was calculated across 369 the whole length of the subject and so mean ALPP was the same irrespective of any distortions; 370 (ii) when measuring fish length the caudal fin is at the same field depth as the background 371 marker, hence there is only a small parallax error caused by the elevation of the snout above 372 the background marker (which resulted in a small overestimate). Using a background fiducial 373 marker will only be accurate when the length of the fish is not elevated above the distal plane 374 however, we propose the general iterative approach to correct parallax errors can equally be

applied (with adjustments) when using a background marker. As with laser and foreground
fiducial markers researchers must ask themselves what may cause the mean ALPP to differ
between the marker and the length being measured.

The choice of marker is context-dependent. Foreground and background markers are relatively inexpensive to use but must be positioned close to the fish. Paired lasers can be projected onto a subject from a distance but become difficult to differentiate in intense broad spectrum visible light (e.g. strong sunlight) or where the surface absorbs or diffuses the wavelength of the laser marker. We suggest that environmental conditions can render laser markers difficult to detect using machine vision.

384 **5** Conclusion

The increasing availability and decreasing costs of robust cameras makes them more attractive to ecological and fisheries researchers. We have developed a mechanistic methodology to achieve accurate estimation of morphometric measurements from 2-D images captured with limited control over the equipment. Increasing the accuracy of length estimation from images using software automation could reduce costs and would increase the potential to collect finer grain data in population assessments, particularly—but not exclusively—in citizen science and other volunteer based projects.

392

## 393 6 References

- Bartholomew, D. C., Mangel, C., Alfaro-shigueto, J., Pingo, S., Jimenez, A., Godley, B. J.,
- 395 ... Godley, B. J. (2018). Remote electronic monitoring as a potential alternative to on-
- board observers in small-scale fisheries. *Biological Conservation*, 219(May 2017), 35–

397 45. https://doi.org/10.1016/j.biocon.2018.01.003

- Bicknell, A. W. J., Godley, B. J., Sheehan, E. V., Votier, S. C., & Witt, M. J. (2016). Camera
  technology for monitoring marine biodiversity and human impact. *Frontiers in Ecology and the Environment*, *14*(8), 424–432. https://doi.org/10.1002/fee.1322
- Bouchet, P. J., & Meeuwig, J. J. (2015). Drifting baited stereo-videography: a novel sampling
  tool for surveying pelagic wildlife in offshore marine reserves. *Ecosphere*, 6(8), art137.
  https://doi.org/10.1890/ES14-00380.1
- 404 Chang, S.-K., DiNardo, G., & Lin, T.-T. (2010). Photo-based approach as an alternative
- 405 method for collection of albacore (*Thunnus alalunga*) length frequency from longline
  406 vessels. *Fisheries Research*, 105(3), 148–155.
- 407 https://doi.org/10.1016/J.FISHRES.2010.03.021
- 408 Claassens, L., & Hodgson, A. N. (2018). Gaining insights into in situ behaviour of an
  409 endangered seahorse using action cameras. *Journal of Zoology*, *304*(2), 98–108.
  410 https://doi.org/10.1111/jzo.12509
- 411 Costa, C., Loy, A., Cataudella, S., Davis, D., & Scardi, M. (2006). Extracting fish size using
- 412 dual underwater cameras. *Aquacultural Engineering*, *35*(3), 218–227.
- 413 https://doi.org/10.1016/J.AQUAENG.2006.02.003
- 414 Deakos, M. H. (2010). Paired-laser photogrammetry as a simple and accurate system for
- 415 measuring the body size of free-ranging manta rays *Manta alfredi*. Aquatic Biology,
- 416 *10*(1), 1–10. https://doi.org/10.3354/ab00258
- 417 Dunbrack, R. L. (2006). In situ measurement of fish body length using perspective-based
  418 remote stereo-video. *Fisheries Research*, 82(1–3), 327–331.
- 419 https://doi.org/10.1016/J.FISHRES.2006.08.017
- 420 Faunce, C. H., & Barbeaux, S. J. (2011). The frequency and quantity of Alaskan groundfish
- 421 catcher-vessel landings made with and without an observer. *ICES Journal of Marine*
- 422 *Science*, 68(8), 1757–1763. https://doi.org/10.1093/icesjms/fsr090
- 423 Fishbrain. (2018). Fishbrain [Web Page]. Retrieved July 19, 2018, from
- 424 https://fishbrain.com/mission/
- 425 Garrido-Jurado, S., Muñoz-Salinas, R., Madrid-Cuevas, F. J., & Marín-Jiménez, M. J. (2014).

- 426 Automatic generation and detection of highly reliable fiducial markers under occlusion.
- 427 *Pattern Recognition*, 47(6), 2280–2292. https://doi.org/10.1016/j.patcog.2014.01.005
- 428 Harvey, E. S., Fletcher, D., & Shortis, M. R. (2001). A comparison of the precision and
- 429 accuracy of estimates of reef-fish lengths made by divers and a stereo-video system.

430 *Fishery Bulletin*, 99(1), 63–71. Retrieved from

- 431 http://www.geomsoft.com/markss/papers/Harvey\_etal2001\_comp\_precacc.pdf
- 432 Hold, N., Murray, L. G., Pantin, J. R., Haig, J. A., Hinz, H., & Kaiser, M. J. (2015). Video
- 433 capture of crustacean fisheries data as an alternative to on-board observers. *ICES*434 *Journal of Marine Science*, 72(6), 1811–1821. https://doi.org/10.1093/icesjms/fsv030
- 435 Hyder, K., Townhill, B., Anderson, L. G., Delany, J., & Pinnegar, J. K. (2015). Can citizen
- 436 science contribute to the evidence-base that underpins marine policy? *Marine Policy*,

437 59(0), 112–120. https://doi.org/10.1016/j.marpol.2015.04.022

- 438 IBM Corp. (2011). IBM SPSS Statistics for Windows. Released 2011. [Computer Program],
- 439 Armonk, NY: IBM. Retrieved from https://www.ibm.com/uk-en/products/spss-statistics
- 440 ICES. (2017). ICES WGRFS Report 2017. Report of the Working Group on Recreational
- 441 *Fisheries Surveys (WGRFS) 12-16 June 2017* [Report]. Azores, Portugal. Retrieved
- 442 from https://www.ices.dk/sites/pub/Publication Reports/Expert Group
- 443 Report/SSGIEOM/2017/WGRFS/wgrfs\_2017.pdf
- 444 Jaquet, N. (2006). A simple photogrammetic technique to measure sperm whales at sea.

445 *Marine Mammal Science*, 22(4), 862–879. https://doi.org/10.1111/j.1748-

- 446 7692.2006.00060.x
- Jeong, S. J., Yang, Y. S., Lee, K., Kang, J. G., & Lee, D. G. (2013). Vision-based automatic
  system for non-contact measurement of morphometric characteristics of flatfish. *Journal of Electrical Engineering and Technology*, 8(5), 1194–1201.
- 450 https://doi.org/10.5370/JEET.2013.8.5.1194
- 451 Loy, A., Boglione, C., Gagliardi, F., Ferrucci, L., & Cataudella, S. (2000). Geometric
- 452 morphometrics and internal anatomy in sea bass shape analysis (*Dicentrarchus labrax*
- 453 L., Moronidae). *Aquaculture*, *186*(1–2), 33–44. https://doi.org/10.1016/S0044454 8486(99)00366-X
- 455 National Oceanic and Atmospheric Administration. (2015a). A Cost Comparison of At-Sea
- 456 Observers and Electronic Monitoring for a Hypothetical Midwater Trawl Herring /
- 457 *Mackerel Fishery*. [Report]. Retrieved from
- 458 https://www.greateratlantic.fisheries.noaa.gov/fish/em\_cost\_assessment\_for\_gar\_herring
- 459 \_150904\_v6.pdf

- 460 National Oceanic and Atmospheric Administration. (2015b). A Preliminary Cost Comparison
- 461 of At-sea Monitoring and Electronic Monitoring for a Hypothetical Groundfish Sector
- 462 [Report]. Retrieved from
- 463 https://www.greateratlantic.fisheries.noaa.gov/stories/2015/september/em\_cost\_assessm
  464 ent\_for\_gar\_multispecies\_2015\_06\_10.pdf
- 465 Neuswanger, J. R., Wipfli, M. S., & Rosenberger, A. E. (2016). Measuring fish and their
- 466 physical habitats : Versatile 2-D and 3-D video techniques with user-friendly software.
- 467 *Canadian Journal of Fisheries and Aquatic Sciences*, *13*(June), 1–48.
- 468 https://doi.org/10.1139/cjfas-2016-0010
- 469 Nguyen, T. X., Winger, P. D., Legge, G., Dawe, E. G., & Mullowney, D. R. (2014).
- 470 Underwater observations of the behaviour of snow crab (*Chionoecetes opilio*)
- 471 encountering a shrimp trawl off northeast Newfoundland. Fisheries Research, 156, 9–
- 472 13. https://doi.org/10.1016/J.FISHRES.2014.04.013
- 473 OpenCV team. (2018). OpenCV: Camera Calibration and 3D Reconstruction [Web Page].
- 474 Retrieved April 23, 2018, from
- 475 https://docs.opencv.org/master/d9/d0c/group\_calib3d.html
- 476 Pauly, D., & Morgan, G. R. (1987). Length-Based Methods in Fisheries Research. In *The*477 *Theory and Application of Length-Based Stock Assessment Methods* (pp. 1–459).
- 478 Mazara del Vallo, Sicily.
- 479 Poli, B. M., Parisi, G., Zampacavallo, G., Mecatti, M., Lupi, P., Gualtieri, M., & Franci, O.
- 480 (2001). Quality outline of European sea bass (*Dicentrarchus labrax*) reared in Italy:
- 481 Shelf life, edible yield, nutritional and dietetic traits. *Aquaculture*, 202(3–4), 303–315.
  482 https://doi.org/10.1016/S0044-8486(01)00780-3
- 483 Rogers, T. D., Cambiè, G., & Kaiser, M. J. (2017). Determination of size, sex and maturity
- 484 stage of free swimming catsharks using laser photogrammetry. *Marine Biology*, *164*(11),
  485 1–11. https://doi.org/10.1007/s00227-017-3241-7
- 486 Rohlf, F. J., & Marcus, L. F. (1993). A revolution in morphometrics. *Trends in Ecology & Evolution*, 8(4), 129–132.
- 488 Rosen, S., Jörgensen, T., Hammersland-White, D., & Holst, J. C. (2013). DeepVision: a
- 489 stereo camera system provides highly accurate counts and lengths of fish passing inside
- 490 a trawl. *Canadian Journal of Fisheries and Aquatic Sciences*, 70(10), 1456–1467.
- 491 https://doi.org/10.1139/cjfas-2013-0124
- 492 Schmid, K., Reis-Filho, J. A., Harvey, E. S., & Giarrizzo, T. (2017). Baited remote
- 493 underwater video as a promising nondestructive tool to assess fish assemblages in

494 clearwater Amazonian rivers: testing the effect of bait and habitat type. *Hydrobiologia*,

495 784(1), 93–109. https://doi.org/10.1007/s10750-016-2860-1

- 496 Schneider, C. A., Rasband, W. S., & Eliceiri, K. W. (2012). NIH Image to ImageJ: 25 years
- 497 of image analysis. *Nature Methods*, 9(7), 671–675. Retrieved from
- 498 http://www.ncbi.nlm.nih.gov/pubmed/22930834
- 499 Struthers, D. P., Danylchuk, A. J., Wilson, A. D. M., & Cooke, S. J. (2015). Action cameras:
- 500 Bringing aquatic and fisheries research into view. *Fisheries*, 40(10), 502–512.
- 501 https://doi.org/10.1080/03632415.2015.1082472
- 502 Szeliski, R. (2010). *Computer Vision: algorithms and applications*. [Book], Springer Science
  503 & Business Media. https://doi.org/10.1007/978-1-84882-935-0
- 504 Tulli, F., Balenovic, I., Messina, M., & Tibaldi, E. (2009). Biometry traits and geometric
- 505 morphometrics in sea bass (*Dicentrarchus labrax*) from different farming systems.
- 506 Italian Journal of Animal Science, 8(SUPPL. 2), 881–883.
- 507 https://doi.org/10.4081/ijas.2009.s2.881
- van Helmond, A. T. M., Chen, C., & Poos, J. J. (2017). Using electronic monitoring to record
  catches of sole (*Solea solea*) in a bottom trawl fishery. *ICES Journal of Marine Science*,
- 510 74(5), 1421–1427. https://doi.org/10.1093/icesjms/fsw241
- 511 Venturelli, P. A., Hyder, K., & Skov, C. (2017). Angler apps as a source of recreational
- 512 fisheries data : opportunities , challenges and proposed standards. *Fish and Fisheries*,
- 513 *18*, 578–595. https://doi.org/10.1111/faf.12189
- 514 VideoLAN. (2018). VLC media player. [Computer Program], VideoLAN. Retrieved from
  515 https://www.videolan.org/vlc/index.en-GB.html
- White, D. J., Svellingen, C., & Strachan, N. J. C. (2006). Automated measurement of species
  and length of fish by computer vision. *Fisheries Research*, 80(2–3), 203–210.
- 518 https://doi.org/10.1016/j.fishres.2006.04.009
- 519 Zhang, Z. (2000). A flexible new technique for camera calibration. *IEEE Transactions on*
- 520 *Pattern Analysis and Machine Intelligence*, 22(11), 1330–1334.
- 521 https://doi.org/10.1109/34.888718
- 522

## 523 **7 Funding**

524 This work was supported by the Fisheries Society of the British Isles under a PhD

525 Studentship granted to GGM. KH was supported by Cefas Seedcorn (DP227AE).

## 526 8 Supplementary Materials

- 527 Supplementary material is available at ICES JMS online; (i) Supplementary materials A, B
- and C are code listings (Python 3.5) of the core functions used for (S1) lens calibration; (S2)
- 529 calculate the standardised mean subject width; (S3) Table 1 variable calculations.

## 530 9 Competing Interests

531 No competing interests to declare