

# Emissions down the drain: Balancing life cycle energy and greenhouse gas savings with resource use for heat recovery from kitchen drains Schestak, Isabel; Spriet, Jan; Styles, David; Williams, Prysor

#### **Journal of Environmental Management**

DOI: 10.1016/j.jenvman.2020.110988

Published: 01/10/2020

Peer reviewed version

Cyswllt i'r cyhoeddiad / Link to publication

*Dyfyniad o'r fersiwn a gyhoeddwyd / Citation for published version (APA):* Schestak, I., Spriet, J., Styles, D., & Williams, P. (2020). Emissions down the drain: Balancing life cycle energy and greenhouse gas savings with resource use for heat recovery from kitchen drains. Journal of Environmental Management, 271, Article 110988. https://doi.org/10.1016/j.jenvman.2020.110988

Hawliau Cyffredinol / General rights Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

• Users may download and print one copy of any publication from the public portal for the purpose of private study or research.

- You may not further distribute the material or use it for any profit-making activity or commercial gain
   You may freely distribute the URL identifying the publication in the public portal ?

Take down policy If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

1 Emissions down the drain: Balancing life cycle energy and

2 greenhouse gas savings with resource use for heat recovery from

- 3 kitchen drains
- 4 Isabel Schestak<sup>a,\*</sup>, Jan Spriet<sup>b</sup>, David Styles<sup>a,c</sup>, A Prysor Williams<sup>a</sup>

<sup>a</sup> School of Natural Sciences, Bangor University, Deiniol Road, LL57 2UW, Bangor, Gwynedd, United
 Kingdom

- <sup>b</sup> Department of Civil, Structural and Environmental Engineering, Trinity College, The University of
   Dublin, College Green, Dublin 2, Ireland
- 9 <sup>c</sup> School of Engineering, University of Limerick, Limerick, V94 T9PX, Ireland.
- 10 \* Corresponding author. *E-mail address*: isabel.schestak@bangor.ac.uk Tel.: +44-1248-383219
- 11

## 12 Abstract

13 Although the food service sector is a major user of water, the potential for heat recovery from commercial kitchens' drain water remains largely unexplored. For the first time, we compare 14 15 the life cycle environmental burdens of producing and installing a heat recovery system with 16 the environmental credits arising from energy savings for a restaurant case study, and for the 17 entire UK food service sector. Life Cycle Assessment was applied to determine the impacts of 18 heat recovery systems made from different materials and comprising a heat exchanger in the 19 shape of a concentric double-walled pipe, pipework and fittings. The design option with the 20 smallest environmental footprint combined a heat exchanger made out of polypropylene-21 graphite (PP-GR) with polyethylene pipework, exhibiting 80-99% less environmental impact 22 compared with components made out of (35% recycled) copper. Contrasting the 23 environmental impacts of two heat recovery set-ups with energy savings shows that a PP-GR 24 based system pays back all seven assessed environmental impacts within two years, while 25 payback times for the copper-based system vary depending on the replaced energy source, 26 and can exceed the 10 year operational lifetime of the system. When looking at typical flow-27 rates in UK food outlets, net environmental savings can be realised across all analysed impact 28 categories above a threshold water consumption of 555 L/day, using current technology. 29 Extrapolation to the UK food service sector indicates annual greenhouse gas emission 30 mitigation potential of about 500 Gg CO<sub>2</sub> equivalent.

31

## 32 Keywords

Environmental impact assessment, wastewater heat recovery, energy savings, eco-design,
 climate change mitigation, recycling

35

## 36 **1 Introduction**

In the UK, nearly half of the water consumption of the wider food and drink sector occurs in
the hospitality and food service sub-sector, with an estimated 143 million m<sup>3</sup> water used in
2010 for the preparation of meals in commercial and similarly used kitchens (BromleyChallenor et al., 2013). Spriet and McNabola (2019a) determined a total wastewater heat

41 recovery potential for the UK food service sector of 1.4 TWh/year, and a financially viable 42 potential of 1.24 TWh/year. The recovered heat is available for direct reuse for pre-heating the 43 cold water supply and can hence directly contribute to the decarbonisation of hot water use. 44 Heating water accounts for a considerable amount of energy consumption across industrial and non-industrial sectors. It is estimated that up to about 90% of the energy requirements 45 46 and related greenhouse gas (GHG) emissions from the domestic water cycle in industrialised 47 countries derive from heating water (Arpke and Hutzler, 2008; DEFRA, 2008; Fagan et al., 2010; Gerbens-Leenes, 2016; Nair et al., 2014; Siddigi and Fletcher, 2015). Sanders and 48 49 Webber (2012) looked into the energy consumption for water use of all sectors in the US, and 50 found that heating for hot water and steam generation dominated water-related energy consumption not only in the residential, but also the commercial and industrial sector. 51 52 Altogether, 47% of the US primary energy consumption in 2010 was due to water and steam 53 applications (Sanders and Webber, 2012).

54 While heat recovery from wastewater has been intensively studied and applied in the 55 residential sector, this is not the case for the food service sector, although the same appliances can be used. The necessary equipment for heat recovery from drain water on a small-scale 56 includes market-ready low-tech options such as in-line, pipe shaped heat exchangers (Ip et 57 58 al., 2018; McNabola and Shields, 2013; Schuitema et al., 2005; van der Hoek, 2011). They have been predominantly studied and installed for use in households or similar domestic 59 60 settings for shower or mixed drain water (Ip et al., 2018; McNabola and Shields, 2013; Schuitema et al., 2005; Słyś and Kordana, 2014; Wong et al., 2010). However, they could also 61 be potentially used with other wastewater types. 62

63 A bonus of heat recovery from commercial kitchens' drain water is a higher daily water use 64 compared to an average household, which for the UK lies in the range of 360 to 12,500 L/day 65 (Spriet and McNabola, 2019a), versus to 349 L/day in homes (EST, 2013). The heat recovery 66 figures by Spriet and McNabola (2019a) equate to an average yearly saving of about 67 5400 kWh per food outlet. Installation of comparable heat recovery systems with showers have been reported to save 127-1880 kWh/year per six showers in a sports facility (Ip et al., 68 69 2018), and 130-508 kWh/year per one shower in a residential building (Wong et al., 2010). 70 The amount of heat energy recovered during the lifetime of the heat recovery system plays an 71 important role not only for financial payback, but also environmental payback for the 72 installation.

73 As with all manufactured products, heat recovery devices carry environmental burdens 74 through their manufacture, installation works, operation and disposal. Significant burdens from 75 manufacture are especially associated with metals such as copper, which is frequently used 76 for plumbing equipment and a preferred material for heat exchangers because of excellent heat conducting properties. It is known that production of copper components generates larger 77 78 environmental burdens compared to steel (Prek, 2004) or plastic (Asadi et al., 2016; Franklin Associates, 2011), with regard to GHG emissions (Franklin Associates, 2011), human health 79 80 and eutrophication impacts (Asadi et al., 2016). Hence, to justify the application of heat 81 recovery devices on resource efficiency and wider environmental grounds, the impacts 82 generated during their life cycle have to be considered. However, there is a lack of studies 83 evaluating in-line heat recovery devices for small-scale applications, and providing the 84 complete picture of environmental impacts through full Life Cycle Assessment (LCA). The 85 most comprehensive related study was published by Ip et al. (2018), who conducted an 86 environmental and economic assessment of an in-line heat exchanger from copper recovering 87 heat from shower drains in a university sports facility. Whilst their LCA study comprised all 88 steps, from cradle to grave (manufacture, use and end-of-life) of the heat exchanger, it only considered the Global Warming Potential (GWP) burden; i.e. GHG emissions. Other impact 89

categories such as resource depletion with material component manufacture were not
included. The study also did not consider the need for additional pipework or fittings that can
be necessary to connect the heat recovery device to a boiler, especially when retrofitting an
existing plumbing system.

94 Here, we apply LCA methodology to determine for the first time the environmental burdens 95 across seven impact categories arising from the manufacture and retrofit installation of a full drain water heat recovery system suitable for use with kitchen drain water. Besides the 96 97 essential heat exchanger, the system consists of the pipework required for connecting the 98 heat exchanger to a boiler and cold water supply, of insulation and fittings. Due to important 99 potential environmental trade-offs associated with copper highlighted in aforementioned studies, we explore the use of recycled copper and of a polymer based material as alternative, 100 101 namely polypropylene-graphite (PP-GR). For pipework, different materials (copper, steel, 102 polyethylene) and different lengths are considered, in order to represent different site-103 dependent conditions.

As the amount of recoverable heat and the benefits derived from avoided water heating significantly influence the environmental sustainability of heat recovery systems, LCA results are compared to energy savings from different sizes of kitchens used for different purposes: the comparison includes savings from a case study restaurant and from commercial kitchens across the UK food service sector. Eventually, extrapolation of the findings to the UK food service sector determines the potential savings on a national level.

## 110 2 Materials and methods

## 111 2.1 Goal and Scope

112 The objective of this study is to provide a comprehensive picture of the environmental burdens 113 of a heat recovery system retrofitted to a commercial kitchen, to identify the steps in the life 114 cycle contributing most to these environmental burdens and to explore the role for alternative materials to mitigate "hotspots" of environmental impacts, and inform eco-design. The LCA 115 116 approach has been chosen for this purpose, following the guidelines of ISO 14040 (ISO, 117 2006). An LCA accounts for resource use and emissions arising during the life of a product or 118 service, starting with resource extraction and mining, and ending with its disposal or alternative 119 end-of-life (EoL) management. In the case of the copper pipe, it includes for instance the 120 mining of the copper ore, through processing of the copper such as melting and extrusion, to 121 recycling into new copper products.

Environmental impacts are classified into different impact categories, with Global Warming 122 Potential (GWP) caused by GHG emissions being the most prominent one. We furthermore 123 124 chose the following environmental impact categories from the set of categories and 125 characterisation methods recommended at midpoint level by the International Reference Life 126 Cycle Data System (ILCD) (EC JRC 2011): Human Toxicity Potential (HTP) and Freshwater 127 Ecotoxicity Potential (FEToxP), as these impacts are associated to mining activities such as 128 copper mining; Mineral, fossil & renewable Resource Depletion Potential (RDP), as nearly all 129 parts of the heat recovery systems assessed are made from finite materials and changes are expected with different recycled material input rates; Freshwater Eutrophication Potential 130 131 (FEP), Acidification Potential (AP), and Photochemical Ozone Formation Potential (POFP), as they are connected to a variety of industrial processes such as mining, fossil fuel combustion 132 in heat and electricity generation as well as transport. Eutrophication is furthermore associated 133 with energy generation from biomass. HTP is presented as sum of both the cancer and non-134

135 cancer toxicity potential. Normalised scores have been obtained in SimaPro, with136 normalisation factors based on Benini et al. (2014).

137 The life cycles of the heat recovery systems are modelled with the software SimaPro (release

138 9.0) (PRé Sustainability, 2018) and using the Ecoinvent (2018) version 3.5 database for the

139 life cycle inventory for the majority of processes (see Supplementary Material S1 for additional

140 databases used).

#### 141 **2.2 System boundaries**

142 The LCAs include all stages from cradle-to-grave, i.e. from the extraction of the raw materials 143 incorporated in the processes chosen from the database until the end of life of the products (Figure 1). No environmental burdens are considered to arise during the use phase, as the 144 145 device itself is passive and not expected to create any emissions. Maintenance (i.e. cleaning) intervals are unknown, and cleaning burdens are estimated to be minor compared to overall 146 147 lifecycle burdens. Packaging and transport are included. Transport is part of both the 148 foreground system and the background system through choice of appropriate processes from 149 the databases (Supplementary Material S1).



150

Figure 1: System boundaries of the LCAs on the heat recovery system (left, shown for the copper system) andextended boundaries for evaluating the savings potential through the replacement of heat energy sources.

## 153 **2.3 Description of the system and inventory**

#### 154 **2.3.1 Overview**

The core part of the heat recovery system is the heat exchanger designed as a concentric 155 156 double-walled pipe which replaces a part of the wastewater pipe. The warm wastewater flows through the inner pipe, while the cold incoming water flows in the opposite direction through 157 158 the outer pipe (counter flow principle, Supplementary Material S2). For a fully functional heat exchanger and maximum heat recovery, the warm drain water has to form a falling film along 159 160 the wall of the inner pipe (Manouchehri et al., 2015). This is enabled through a vertical installation (Manouchehri et al., 2015). The heat exchanger is connected to the existing 161 162 pipework via plastic fittings (bottom and top connectors) with joint rings, one fitting each end

- of the pipe (BPD ltd., 2019a). Screws and brackets made from steel and rubber fix the heatexchanger at the wall (BPD ltd., 2019a).
- The pre-heated incoming water is led from the heat exchanger to the conventional heating system, usually a boiler, for further heating. Depending on the layout of the existing plumbing in a building, the heat exchanger cannot be placed in close vicinity to the boiler or the incoming cold water pipe and additional pipework can be required to cross the distance. To minimise heat loss, the pipework is considered to be insulated with a layer of synthetic rubber.
- 170 An overview of the inventory is provided in the Supplementary Material S1.

#### 171 **2.3.2** Manufacture of the copper heat exchanger

- 172 Description: The heat exchanger considered refers to a model which is 1.68 m long, has an 173 inner diameter of 48 mm and weighs 6.1 kg (Q-Blue b.v., 2018). The capacity for the drain 174 water flow is 50 L/min, and the maximum clean water flow is 12 L/min. The clean water void 175 between the inner and outer cylinder has a volume of 0.39 L.
- 176 Modelling: Starting with primary or recycled copper, the production of a semi-finished copper 177 tube continues with the following steps: melting, casting, extrusion, drawing and finishing steps 178 from the raw pipe to the final heat exchanger (Tikana et al., 2005). As the processes of melting and casting are already included in an Ecoinvent database process for primary copper 179 180 production, they are only modelled separately for the recycled copper. For melting the 181 secondary copper, we assume the electricity input for an induction furnace, which is the type of furnace predominantly used in the copper industry (CDA Inc., 2019). The energy 182 183 requirement for melting of copper in an induction furnace is calculated according to basic 184 physical principles and a plant efficiency of 70% (Dötsch, 2017) (Supplementary Material S3).
- As primary copper production is a resource- and energy-intensive process, responsible for considerable emissions during mining, ore refining and further processing (Althaus and Classen, 2005; Castro Molinare, 2014), adequate assumptions for the share of recycled copper in the heat exchanger are necessary for a realistic picture of its environmental impacts. Two types of recycled or secondary copper can be distinguished: recycled scrap, which originates from low grade copper scrap and which has to be refined electrolytically before reuse; and clean scrap, which can be directly re-melted.
- Studies from Ciacci et al (2017) and Glöser et al (2013) estimated an average 35% recycling input rate for all types of copper products in Europe and globally, of which 63% is clean scrap. Another study, commissioned by the copper industry and claiming to rely on primary industry data, assumes a share of around 70% of recycled copper as input for the production of European copper pipes, of which about 90% comes from clean scrap (Tikana et al., 2005).

#### 197 2.3.3 Manufacture of the PP-GR heat exchanger

198 PP-GR has been chosen in this study as a potential substitute for copper in a wastewater heat 199 exchanger for several reasons. It exhibits a greater fouling and corrosion resistance compared 200 to metals, which is important when conveying media heavily loaded with organic material, such 201 as kitchen wastewater (Chen et al., 2016; Hussain et al., 2017, Glade et al., 2018). As PP-GR has been tested and designed for use in highly corrosive environments such as desalination 202 203 plants and with higher temperatures than those of kitchen wastewater, we expect the material 204 to be appropriate to handle wastewater (Glade et al., 2018; Technoform, 2014). From an 205 environmental perspective, a great advantage is the smaller amount of energy required for 206 forming polymers, compared with metals.

207 Description: There is no commercially available heat exchanger made from PP-GR to date 208 that is equivalent to the copper model evaluated here. Material requirements are therefore 209 calculated for a hypothetical heat exchanger with the same length and volume for the water 210 leading parts in order to compare the amount of recovered heat. As PP-GR has a considerably lower density than copper, at 1.56 g/cm<sup>3</sup>, only 1.02 kg material is required. The PP-GR 211 212 composite is made of polypropylene as a matrix with graphite as filler, imparting a thermal 213 conductivity comparable to that of stainless steel (Glade et al., 2018). PP-GR contains 72 wt% 214 graphite, equalling 50 vol% (Glade et al., 2018).

Modelling: Information on the material composition and properties were attained from a manufacturer (Technoform, 2014) as well as from a study on its mechanical, chemical and thermal properties (Glade et al., 2018). Virgin polypropylene and battery grade graphite are considered as the inputs for the PP-GR pipe. Battery grade graphite production requires energy intensive steps, comes with a higher environmental burden than that for graphical paper and is therefore selected as a conservative proxy, so as not to underestimate environmental burden (Olson et al., 2016). The tube is produced through an extrusion process.

In contrast to the copper device, no field data are available for the heat recovery potential of
the PP-GR heat exchanger in the discussed application. But given a heat transfer coefficient
of the PP-GR tube of 2523 W/(m<sup>2</sup>\*K) (Technoform, 2014), we can determine an effectiveness
of 60.5%, close to that of the copper heat exchanger of 58% on average, according to the
manufacturer (Q-Blue b.v. 2018, Spriet and McNabola, 2019a) (Supplementary Material S4).
Heat recovery potential by the PP-GR device is therefore conservatively assumed to be equal
to that for copper.

### 229 **2.3.4 Pipework**, insulation, fittings and packaging

230 Pipework required to retrofit the heat exchanger within the existing plumbing network is also 231 accounted for. The outer diameter of this pipework is 28 mm (DN25), and we consider three 232 lengths to represent different retrofit situations: 1 m, 10 m (the length required in the case study), and 30 m. Copper, steel and polyethylene are compared as pipe materials. Information 233 234 to model the pipework was retrieved from pipe manufacturers for copper (German Pipe, 2019), 235 polyethylene (Pipelife UK, 2019) and stainless steel (Geberit Sales Ltd, 2019). The insulation 236 is modelled using a pipe insulation module from Ecoinvent, which refers to insulation made 237 from the synthetic rubber ethylene propylene diene methylene (EPDM). Information on the 238 quantities and types of material of the fittings were derived from a manufacturer and a supplier 239 (BPD ltd., 2019b; Q-Blue b.v., 2018). The weights of the parts and packaging were determined 240 directly by the authors.

### 241 2.3.5 Transport

242 The city of Birmingham has been chosen as a representative, central location within the UK for installation of the heat recovery system. The copper heat exchanger and the fittings are 243 244 considered to be shipped from the Netherlands to the UK by lorry, unless more specific 245 information has been provided by a supplier for particular fittings (Livingston, 2018). Two parts 246 of the top connector are produced in Poland, and the third part is made in the UK along with the entire bottom connector. The PP-GR heat exchanger in contrast is shipped from the 247 production site in Kassel, Germany. The pipework and insulation is assumed to originate from 248 Germany. The transport from the site of use to a recycling facility or landfill site is considered 249 250 using a generic distance of 100 km.

#### 251 2.3.6 End-of-Life

252 The LCAs regard recycling for parts where a recycling infrastructure exists in the UK, and landfill where recycling is unlikely. Different methodologies exist to allocate burdens for 253 254 recyclable materials in LCA (Ekvall and Tillman, 1997; Johnson et al., 2013). Here, we opt for 255 the cut-off or recycled content approach (Johnson et al., 2013) and hence do not account for 256 emissions and benefits from recycling in the EoL stage, as the recycling benefits and burdens in the manufacturing stage are already taken into account, where applicable. For copper, we 257 258 assume recycling of 80%, which is the EoL processing rate for European plumbing equipment 259 as determined by Ruhrberg et al. (2006). The remaining copper is considered to go to landfill. 260 Bottom and top connectors are recycled completely, as their size allows for municipal waste 261 management for hard plastics. Brackets and screws are assumed to go to landfill, as it is 262 unlikely that the user will deconstruct and separate these small components to allow for 263 recycling. For insulation, material is considered to be sent to a landfill for disposal (BIF REP, 264 2013). Pipework: Copper pipework follows the same EoL route as the heat exchanger from 265 copper. Steel is recycled at a rate of 70% (Davis et al., 2006) and polyethylene EoL is split 266 into recycling (16%), incineration (35%) and landfill (49%) (Mudgal et al., 2011) (see 267 Supplementary Material S1 for details).

As the PP-GR composite is a relatively new material on the market, we conservatively assume landfill as the most likely fate, accounting for both polypropylene and the inert graphite.

#### 270 2.4 Scenarios and functional unit

A range of scenarios has been adopted for the setup of the heat recovery system in order to represent various installation settings and compare different design options. The five scenarios are listed in Table 1. They all include the functional unit of a heat recovery system with one in-line heat exchanger, pipework of 10 m length and fittings. Separate from these scenarios, we assess the design options for the pipework, comparing copper, steel and polyethylene pipework and lengths of 1, 10 and 30 m.

Scenario	Name	Number of heat exchangers	Material heat exchanger	Material pipework	Length pipework
1	Copper (0%)	1	Copper (0% recycled content)	Copper (0% recycled content)	10 m
2	Copper (35%)	1	Copper (35% recycled content)	Copper (35% recycled content)	10 m
3	Copper (70%)	1	Copper (70% recycled content)	Copper (70% recycled content)	10 m
4	Copper (35%) + PE	1	Copper (35% recycled content)	Polyethylene	10 m
5	PP-GR + PE	1	Polypropylene-graphite (PP- GR)	Polyethylene	10 m

277 Table 1: Overview of assumptions for scenarios of the LCAs.

278

For the operational lifetime, we assume a conservative duration of 10 years. Other studies considered a 50-year lifetime for a copper heat exchanger or copper pipework (Asadi et al., 2016; Ip et al., 2018), but damage through corrosion is likely to occur earlier with kitchen wastewater as it carries a greater load of organic pollutants than shower drain or clean water. The functional unit for the case of an average UK kitchen is 1 kWh of water heating delivered through heat recovery.

#### 285 2.5 Savings potential

In order to determine the potential environmental savings associated with use of the heat
 recovery system, data on recovered heat are required. We look at two different cases:

288 Case study: Firstly, LCA results are set into context with data on heat recovery from a case 289 study on the restaurant kitchen of Penrhyn Castle in Bangor, North Wales, UK, which is open 290 to visitors as a tourist attraction. Spriet and McNabola (2019b) predicted the amount of 291 recovered heat during an 8-month monitoring study to be 8.45 kWh per day, taking into 292 account the following: a copper heat exchanger as described above, a measured average 293 daily water consumption of 652.5 L, a 90% return rate of the consumed water into the drain, a 294 retention time of water through kitchen appliances of no longer than 1 hour and measured average drain water temperatures of 25 to 35 °C (Supplementary Material S4). As the 295 296 pipework is insulated and as time between heat recovery and consumption of the pre-heated water is very short, heat losses in the pipe are considered negligible. We consider the 297 298 restaurant to be open 310 days a year. The environmental impacts realised through heat 299 recovery are compared to the avoided impacts when replacing different conventional and 300 renewable energy sources for water heating: natural gas, UK grid electricity, woodchips, geo 301 and solar thermal energy, and the energy mix for water heating in the UK service sector (BEIS, 302 2018) (Table 2; Supplementary Material S5 for environmental burdens from the energy mix). Results are presented as payback times for heat recovery when it replaces the mentioned 303 304 energy sources.

Life cycle burdens of the heat recovery systems as in scenario 2 and 5 are considered. Scenario 2 represents the actual installations carried out at the case study site where only copper equipment was used. Scenario 5 has been selected to show potential savings with polymer-based materials.

Table 2: Types of energy and respective database modules used for determination of environmental savings
 through heat recovery

Energy type	Database module	Database	Share in UK water heating mix [%]*
Natural gas	Heat, central or small-scale, natural gas {Europe without Switzerland}  market for	Ecoinvent	66
Grid electricity	Electricity, low voltage {GB}  market for	Ecoinvent	14
Oil	Heat, central or small-scale, other than natural gas {Europe without Switzerland}  heat production, light fuel oil, at boiler 10 kW condensing, non-modulating	Ecoinvent	12
Softwood chips	Heat, central or small-scale, other than natural gas {CH}  heat production, softwood chips from forest, at furnace 50 kW, state-of-the-art 2014	Ecoinvent	4
Hardwood chips	Heat, central or small-scale, other than natural gas {CH}  heat production, hardwood chips from forest, at furnace 50 kW, state-of-the-art 2014	Ecoinvent	1
Straw	Heat, district or industrial, other than natural gas {GLO}  heat production, straw, at furnace 300 kW	Ecoinvent	3
Geothermal	Heat, borehole heat pump {Europe without Switzerland}] heat production, borehole heat exchanger, brine-water heat pump 10 kW	Ecoinvent	n.a.
Solar thermal	Heat, central or small-scale, other than natural gas {CH}  operation, solar collector system, evacuated tube collector, one-family house	Ecoinvent	n.a.

\*current UK energy mix for heating water in the service sector (BEIS, 2018). The category "biomass" was split into softwood chips, hardwood chips and straw in order to best reflect the current use of biomass heat sources (BEIS 2018b, Forest Research 2018, DEFRA 2017). Neglected: bioenergy from (unless included in grid electricity): landfill gas, sewage gas, waste wood, animal biomass, anaerobic digestion and biodegradable energy from waste.

311

**UK commercial food outlets:** Secondly, we determine the environmental sustainability of a heat recovery system when used with typical water consumption rates prevalent in UK commercial food outlets. The water consumption rates refer to the average rates of different food outlet categories (Spriet and McNabola, 2019a), ranging from 360 to 12,500 L/day. Heat recovery data were determined as in Spriet and McNabola (2019a), (Supplementary Material S4), taking into account the number of heat exchangers optimised for maximum financial payback with 310 open days a year over a 10 year lifetime i.e. for greater flow-rates, the

- installation of several heat exchangers in parallel is considered (Supplementary Material S6).
- 320 The life cycle burdens taken into account for the heat recovery system refer to scenario 4.
- Finally, data on the number of served meals, water consumption and the number of outlets in the hospitality and food service sector serve to extrapolate the environmental savings to a UK level (Backman, 2018; Bromley-Challenor et al., 2013; Spriet and McNabola, 2019a).

## 324 **3 Results and Discussion**

#### 325 3.1 Life Cycle Assessment results

326 Figure 2 shows the characterised LCA results of all scenarios for the drain water heat recovery 327 system. The different materials used for the scenarios lead to large differences between their footprints. There are clear benefits from increasing the share of recycled copper or fully 328 329 replacing copper with polymer materials. Production, use and end-of-life of the copper systems 330 emit 87, 81 and 71 kg of CO<sub>2</sub> equivalent, respectively, depending on the recycled material input. These numbers coincide with the findings of Giurco and Petrie (2007) who found an 331 332 increase in recycling rates besides demand reduction the only strategy to meet GHG reduction targets for copper production as ever lower ore grades constrain the potential to decarbonise 333 334 copper ore processing.

A combination of a copper heat exchanger with polyethylene pipework has a GWP of 39 kg CO<sub>2</sub> equivalent. Reductions in burdens of around 45-50% can be achieved for HTP, FEP, FEtoxP and RDP, when switching from a heat exchanger and pipework of zero percent recycled copper to one of 70% recycled copper. Replacement of the 35%-copper pipework through PE can lower the impacts of the whole system by 50-60% considering the heat exchanger is still made from 35%-copper. Scenario 4 therefore represents the most environmentally friendly material combination currently available on the market for this set-up.



Figure 2: Environmental burdens arising from the life cycle of drain water heat recovery systems consisting of inline heat exchanger, 10 m pipework, fittings and insulations. Percentage in brackets stands for the share of
recycled copper. PE: polyethylene, PP-GR: Polypropylene-Graphite. GWP: Global Warming Potential; HTP:
Human Toxicity Potential; POFP: Photochemical Ozone Formation Potential; AP: Acidification Potential; FEP:
Freshwater Eutrophication Potential; FEToxP: Freshwater Ecotoxicity Potential; RDP: Mineral, fossil & renewable
Resource Depletion Potential. All scenarios as described in Table 1.

348 Still though, a purely polymer based system with PP-GR performs considerably better with a 349 GWP of only 16 kg CO<sub>2</sub> equivalent. Depending on the category, it exhibits only 1-20% of the 350 impacts of the 35%-copper scenario. Supplementary Material S7 shows the scenarios in a relative comparison to each other. The normalised results allow for inter-category comparison
and show that the most relevant contributions are those to HTP and FEToxP for both systems
(Supplementary Material S8).

354 Ip et al. (2018) determined a GWP of 56 kg CO<sub>2</sub> equivalent for their copper heat exchanger, 355 which would compare to 26, 29 or 32 kg CO<sub>2</sub> equivalent for the life cycle of our copper heat 356 exchanger alone with 70, 35 or 0 % recycled content, respectively (excluding pipework). Their 357 study does not state the recycled copper input, making direct comparison difficult. Even so, 358 one reason for the different results is certainly the different material requirement for the heat 359 exchanger, with about 25 kg copper in Ip's study and about 6 kg in this study.

360 Figure 3 shows the relative contribution of the life cycle stages to the environmental burdens of heat recovery systems under scenario 2 and 5. The majority of burdens of the copper 361 362 system across all categories originate from manufacture of copper parts (heat exchanger and pipework), ranging from 87% of GWP burdens to 99% of HTP, FEP and FEtoxP burdens. This 363 364 underlines the pollution associated with the extraction and manufacture of copper products discussed earlier in the introduction (Althaus and Classen, 2005; Castro Molinare, 2014). 365 366 Indeed, the main burdens from the manufacture of heat exchanger and pipes derive from the 367 generation of primary copper (Ecoinvent, 2018): HTP causing emissions arise mainly during 368 the treatment of sulfidic tailings from primary copper production and comprise groundwater 369 polluting zinc and arsenic (HTP non-cancer), and chromium VI (HTP cancer), amongst others. 370 Similarly, FEToxP is mainly caused by zinc and copper emissions from tailing treatment and 371 FEP predominantly through phosphate released into groundwater during the same process 372 (Ecoinvent, 2018). The main substances responsible for POFP are nitrogen oxides emitted 373 into the air during blasting, which also releases sulphur dioxide, the major cause for AP. 374 Resource depletion is caused especially by use of the sulfidic copper ore and molybdenum 375 during primary copper generation. Other resources contribute less than 1% to the RDP, hence 376 RDP is almost exclusively due to the consumption of abiotic materials. Only for GWP, the 377 finishing process of the heat exchanger and pipes has a greater influence than primary copper production driven by heat and electricity consumption. The impact from the pipework is greater 378 379 than that from the heat exchanger, which is due to greater material use for the 10 m pipework (11 kg vs. 6 kg copper). 380

381 In the PP-GR system, the manufacture of the heat exchanger and pipework plays a comparatively smaller role. Apart from transport, all components make significant 382 383 contributions to the lower overall impacts, depending on the category. Manufacture of the 384 insulation from EPDM rubber accounts for 14-90% of burdens, with the greatest contribution 385 going to RDP. The main resource depleted is indium during the operation of the zinc mine, zinc being an ingredient for the production of EPDM (Ecoinvent, 2018). EoL stage is mainly 386 responsible for impacts in FEToxP (64%), HTP (29%) and GWP (16%). FEToxP causing 387 388 emissions in the EoL stage are arising from incineration and landfilling of the pipe material PE, both processes releasing vanadium into groundwater (Ecoinvent, 2018). The contribution of 389 390 the predominantly cardboard packaging ranges from 4% (RDP) to 22% (FEP) across 391 categories.



#### 392

Figure 3: LCA of heat recovery systems (scenarios 2 and 5): Relative contribution of the life cycle stages to the
environmental impacts of the two heat recovery systems including 10 m pipework. Left: scenario 2: copper
system with 35% recycled copper input. Right: scenario 5: PP-GR composite system with PP-GR heat exchanger
and pipework from PE. GWP: Global Warming Potential; HTP: Human Toxicity Potential; POFP: Photochemical
Ozone Formation Potential; AP: Acidification Potential; FEP: Freshwater Eutrophication Potential; FEToxP:
Freshwater Ecotoxicity Potential; RDP: Mineral, fossil & renewable Resource Depletion Potential; Hex: Heat
exchanger; EoL: End of Life.

400 The length of the pipework greatly influences the overall LCA results. Figure 4 shows the 401 burdens from heat exchanger and pipework separately. Burdens for long and metal based 402 (steel or copper) pipework can be greater than those from the heat exchanger. Steel pipe 403 burdens are considerably lower than copper pipe burdens, ranging from 89% (FEtoxP) to 15% 404 (GWP) of those from copper (see Supplementary Material S9 for more impact categories). These results underline the importance of considering the full equipment necessary for retrofit, 405 and also how on-site conditions influence the environmental sustainability of a retrofit 406 measure. As far as we are aware, this is the first LCA study of a heat recovery system to 407 408 consider all associated retrofit pipework.



#### 409

Figure 4: Comparison of LCA results for the heat exchanger and pipework for (clockwise from top left): global
warming potential (GWP), resource depletion potential (RDP), freshwater ecotoxicity potential (FEtoxP) and
human toxicity potential (HTP). Left two bars: complete life cycle of a heat exchanger system without pipework.
Right three bars: life cycle of pipework from polyethylene (PE), steel and copper (35% recycled content).

#### 414 **3.2** Environmental savings through heat recovery

#### 415 **3.2.1 Environmental savings in the case study**

In the Penrhyn Castle case study, all environmental burdens from the heat recovery system 416 417 (scenario 2) will be paid back within 10 years when electricity, geo or solar thermal energy or 418 the energy mix for water heating is replaced (Table 3). If the recovered heat replaces natural gas, the impacts of HTP, FEP, FEtoxP and RDP from production, installation and EoL of the 419 420 heat exchanger and pipework will not be fully paid back in the conservative 10-year lifetime considered in this study. The low FEToxP and RDP of wood heating also prevent payback in 421 422 the FEtoxP and RDP categories through heat recovery if wood is used for water heating. For GWP, relatively short payback times of under 1.6 years compared with all energy alternatives 423 can be achieved. The payback time for GWP compared to natural gas, the most common 424

water heating source, is only 0.12 years. This is shorter than the 0.55-1.33 year GWP payback
previously calculated for shower heat recovery (Ip et al., 2018). It underpins the suitability of
kitchens for drain water heat recovery due to typically higher wastewater flow-rates than in
showers.

#### As the burdens of the PP-GR heat recovery system are substantially lower, they are paid back during shorter periods of operation, within 2 years for all impact categories (Table 3).

Table 3: Environmental payback times in years for the heat recovery system of the Penrhyn Castle case study.
Comparison of the copper (35% recycled content) and the PP-GR systems including 10 m of pipework with
different energy sources for water heating. Bold and italic: Impacts are not paid back within a 10-year lifetime. NG
antural gas. Mix: Current UK Energy mix for heating water in the service sector (BEIS, 2018). GWP: Global
Warming Potential; HTP: Human Toxicity Potential; POFP: Photochemical Ozone Formation Potential; AP:
Acidification Potential; FEP: Freshwater Eutrophication Potential; FEToxP: Freshwater Ecotoxicity Potential;

437 RDP: Mineral, fossil & renewable Resource Depletion Potential. Energy sources as in Table 2.

Impact category	NG	Electricity	Wood	Geo	Solar	Mix
Copper (35%)			[ye	ears]		
GWP	0.12	0.06	0.29	0.23	1.58	0.11
HTP	18.87	1.22	2.13	3.76	3.20	5.04
POFP	0.72	0.13	0.27	0.61	2.05	0.40
AP	1.82	0.16	1.19	0.60	1.90	0.68
FEP	12.20	0.59	8.79	1.10	3.31	3.19
FEtoxP	14.16	0.52	11.78	1.72	3.51	3.02
RDP	14.32	2.94	33.49	8.41	3.63	9.23
PP-GR + PE			[ye	ears]		
GWP	0.02	0.01	0.05	0.04	0.27	0.02
HTP	0.16	0.01	0.02	0.03	0.03	0.04
POFP	0.08	0.01	0.03	0.07	0.23	0.04
AP	0.10	0.01	0.07	0.03	0.11	0.04
FEP	0.19	0.01	0.13	0.02	0.05	0.05
FEtoxP	0.25	0.01	0.21	0.03	0.06	0.05
RDP	0.73	0.15	1.71	0.43	0.19	0.47

438

#### 439 **3.2.2** Environmental savings in UK commercial food outlets

440 Two different flow-rates, representing the bottom and top end of the flow-rate spectrum in 441 typical UK food outlets, are taken to show a worst- and best-case scenario for environmental 442 impacts from heat recovery. The best case refers to kitchens with the highest water flow-rate 443 typically found in UK food outlets (12,500 L/day), highest heat recovery potential and therefore 444 the lowest impacts per kWh ("H recov. Low"). The opposite applies to the worst-case scenario 445 with a flow-rate of 360 L/day ("H recov. High"). The environmental burdens for the heat 446 recovery system are based on scenario 4 (Table 1), including one heat exchanger for the low-447 flow option and four heat exchangers in parallel for the high-flow option.



448 Figure 5: Environmental impacts per kWh for water heating. Comparison of heat recovery from drain water with 449 other renewable and non-renewable heat sources, including the current UK energy mix for water heating ("mix"). 450 Burdens of the heat recovery system as in scenario 4 with two different water flow-rates found in UK commercial 451 food outlets. H recov. Low: low impact case due to higher flow-rate of 12,500 L/day. H recov. High: high impact 452 case due to lower flowrate of 360 L/day. NG: natural gas, electricity: UK grid mix, wood: wood biomass 453 combustion, geo: geothermal, solar: solar thermal. GWP: Global Warming Potential; HTP: Human Toxicity 454 Potential; POFP: Photochemical Ozone Formation Potential; AP: Acidification Potential; FEP: Freshwater 455 Eutrophication Potential; FEToxP: Freshwater Ecotoxicity Potential; RDP: Mineral, fossil & renewable Resource 456 Depletion Potential.

Figure 5 displays the environmental impacts for providing 1 kWh for water heating through heat recovery versus other energy sources. Considering global warming, heating water through the use of recovered heat exhibits the lowest emissions with about 0.4 to 4 g CO<sub>2</sub> equivalent/kWh for the low and high impact scenario, respectively. This compares to 461 emissions of 20 to 550 g CO<sub>2</sub> equivalent/kWh for solar thermal and electric water heating – 462 i.e. even when currently available heat recovery technology replaces renewable energy 463 sources, GWP can be reduced. Also for ozone formation and acidification, heat recovery at both flow-rates leads to impact savings compared to all other heat sources. In the other 464 categories, environmental sustainability of heat recovery depends on the flow-rate or the 465 466 heating source replaced. For HTP and FEP, natural gas water heating can have lower 467 environmental impacts compared to heat recovery at low flow-rates. Here, emission savings through heat recovery are only achieved from a flow-rate of about 750 L/day onwards (HTP) 468 469 and 555 L/day (FEP) (values not shown in graph). Similarly, FEtox and RDP can be reduced 470 through heat recovery at higher flow-rates only, when replacing natural gas or wood biomass. With these results a recommendation for drain water heat recovery can be given from a daily 471 472 flow-rate of 750 L when natural gas is replaced, the most common source for water heating in 473 the UK.

474 Figure 6 shows the environmental savings that can be achieved during 10 years of heat 475 recovery depending on the flow-rate and replacing the water heating energy mix. Values are shown as normalised scores. The net environmental savings increase with water 476 477 consumption, although the number of heat exchangers and with them the environmental 478 footprint of the installations augments, too. Apart from RDP, environmental payback is reached 479 within 10 years for all impact categories starting from the lowest average daily water 480 consumption considered (360 L/day) (Spriet and McNabola, 2019a). For RDP, environmental 481 payback within 10 years is only achieved at water consumption rates above approximately 555 L/day or 300 m<sup>3</sup>/year. The greatest normalised savings are achieved in HTP and FEtoxP, 482 483 followed by GWP, AP, RDP, POFP and FEP in descending order.



484

Figure 6: Normalised net environmental savings (positive values) through heat recovery from a commercial
kitchen after 10 years depending on the yearly water consumption. GWP: Global Warming Potential; HTP:
Human Toxicity Potential; POFP: Photochemical Ozone Formation Potential; AP: Acidification Potential; FEP:
Freshwater Eutrophication Potential; FEToxP: Freshwater Ecotoxicity Potential; RDP: Mineral, fossil & renewable

489 Resource Depletion Potential.

Extrapolation of the savings using average daily water consumption rates for the circa 258,000
food outlets in the UK (Backman, 2018; Bromley-Challenor et al., 2013; Spriet and McNabola,
2019a) gives the potential annual environmental savings for the UK (Table 4). Annual GHG
emission mitigation of 490 Gg (kilo-tonnes) CO<sub>2</sub> equivalent could be avoided if heat from

494 wastewater was recovered across all UK commercial food outlets. These environmental
 495 savings equate to 30% of thermal energy needed for water heating in the hospitality and food
 496 service sector, based on the share of hot water consumed in the Penrhyn Castle restaurant
 497 case study.

The results show that even with the currently available copper heat exchanger and especially at high water consumption rates, there is strong evidence for environmental savings. It can

500 therefore be recommended as a viable measure to de-carbonise water heating in commercial kitchens

501 kitchens.

502 Table 4: Yearly net environmental savings potential for the UK through heat recovery from wastewater in all 503 commercial food outlets. eq = equivalent

Impact category	GWP	HTP	POFP	AP	FEP	FEtoxP	RDP
Unit	[kt CO2 eq]	[CTUh]	[t NMVOC eq]	[1000 molc H+ eq]	[t P eq]	[10^6 CTUe]	[kg Sb eq]
All outlets	490	78	772	1390	70	2979	3370

504

Although an economic evaluation of the heat recovery system is out of scope of this study, it is worth mentioning that heat recovery is not only beneficial from an environmental point of view, but also pays back financially from water consumption rates of 960 L/day (Spriet and McNabola, 2019a).

A study by McNabola and Shields (2013) estimated the heat recovery potential from shower drain water in Ireland to be 808 GWh per year, averaging 577 kWh per year for a 3-person household. Taking into account the population of the UK of 66M (ONS, 2019) and the UK domestic energy mix for water heating (BEIS, 2018), this would translate to yearly savings of 13 TWh or 3600 Gg CO<sub>2</sub> equivalent. Based on the heat recovery system evaluated in this study, the aforementioned annual heat recovery at a household scale would not be financially

515 viable, nor environmentally responsible from a resource depletion perspective.

## 516 **3.3 Outlook**

### 517 **3.3.1 Expected changes with a changing energy mix**

518 With a change in the future energy mix towards more renewable sources, the benefit of saving 519 energy through heat recovery is likely to shift from avoiding GHG emissions, to avoiding the 520 depletion of metal and mineral resources. GHG emission savings through heat recovery will 521 be lower as water heating from renewable energy sources emits less GHGs, for both direct 522 electric water heating and thermal water heating with solar collectors or air and ground-source 523 heat pumps (Clarke et al., 2008). Although of course, the GHG emissions of producing the 524 heat recovery system and pipework are also expected to decrease owing to decarbonisation 525 of energy supplies.

Resource depletion burdens are higher for renewable electricity generation (namely wind, solar and hydro power) compared to energy supply from fossil resources owing to large quantities of abiotic resources, especially metals (e.g. manganese, copper, iron, nickel, chrome) required in renewable energy infrastructure (Berrill et al., 2016; Gallagher et al., 2019). The trade-offs between resource depletion and GHG emission savings which currently exist for heat recovery at low flow-rates are therefore likely to disappear.

532 Another important indirect and long-term benefit of heat recovery lies in increasing the 533 efficiency in which energy is used and thus supporting a transformation to a sustainable 534 energy economy through reducing energy demand – a strategy that has been adopted as part of European and UK policies for future low-carbon energy supply (Clarke et al., 2008; da Graça
Carvalho, 2012; Ekins and Lees, 2008; Rosenow, 2012).

## 537 **3.3.2 Recommendation for further research**

As neither the copper nor the PP-GR heat exchanger have been in use with kitchen drain 538 539 water for significant periods of time, there is room for further research and need for empirical 540 data on real performance. In addition to environmental savings during manufacture, PP-GR and similar composites can offer other potential advantages such as the reduction of scaling 541 542 in the pipe and thus reduced build-up of an insulating layer inhibiting heat transfer. The 543 behaviour of new materials for this application, but also the behaviour of the conventional 544 copper heat exchanger when used with heavily polluted wastewater such as that from 545 kitchens, requires long-term experimental studies. This will provide more reliable data on heat 546 transfer performance and on required maintenance interventions such as cleaning to remove 547 scaling or fouling. It will also allow more accurate determination of the useful lifetime of the 548 heat exchangers, which will be important for both economic and environmental performance. The lack of accurate data sets and reliance on manufacturer data for modelling the PP-GR 549 550 material are aspects which should improve with increasing use of such materials.

## 551 **4 Conclusions**

552 The presented LCA study is the first to evaluate the environmental sustainability of a heat 553 recovery system for harvesting the heat of commercial kitchens' drain water, based on case 554 study data. Different sets of materials are studied for the system, comparing components from 555 conventional copper with alternatives from polypropylene and graphite, as well as 556 polyethylene. The results support the following conclusions:

- The environmental impacts from the copper system, predominantly arising from the production of primary copper, can be reduced substantially through increasing the share of recycled copper as input material.
- A critical factor influencing the material requirement and environmental footprint of any retrofitted (or new) heat recovery system is the length of pipework necessary for connecting the heat exchanger with boiler and cold water supply. We therefore recommend to design the system as compact as possible.
  - It is strongly encouraged to consider material choice during the design phase of such installations, including the use of recycled material or new functional materials, such as the polypropylene-graphite composite.
- Heat recovery shows environmental trade-offs with other water heating sources only
   for flowrates at the lower end of the spectrum of typical water consumption rates in UK
   food outlets, mainly for resource depletion.
- The amount of recovered heat and with it the environmental savings increase with the water consumption rate, even when environmental capital costs are increased through the installation of several heat exchangers in parallel. Environmental savings across all seven impact categories analysed is achieved for water consumption above 574 555 L/day when replacing the heating energy mix.
- Heat recovery from wastewater from food outlets offer a potential solution for saving
   energy and emissions across the food service sector. When applied across all UK food
   outlets, GHG emission savings can amount 490 Gg CO<sub>2</sub> equivalent per year.
- 578

564

565

566

580 **Acknowledgement:** This research is part of the *Dŵr Uisce* project, which aims at improving 581 the long-term sustainability of water supply, treatment and end-use in Ireland and Wales. The 582 project has been supported by the European Regional Development Fund (ERDF) Interreg 583 Ireland-Wales Programme 2014-2020.

584

#### 585 **References**

- Althaus, H.J., Classen, M., 2005. Life cycle inventories of metals and methodological
  aspects of inventorying material resources in ecoinvent. Int. J. Life Cycle Assess. 10,
  43–49. https://doi.org/10.1065/lca2004.11.181.5
- 589 Arpke, A., Hutzler, N., 2008. Domestic Water Use in the United States: A Life-Cycle 590 Approach. J. Ind. Ecol. 10, 169–184. https://doi.org/10.1162/108819806775545312
- Asadi, S., Babaizadeh, H., Foster, N., Broun, R., 2016. Environmental and economic life
  cycle assessment of PEX and copper plumbing systems: A case study. J. Clean. Prod.
  137, 1228–1236. https://doi.org/10.1016/j.jclepro.2016.08.006
- 594 Backman, P., 2018. The Foodservice Market. London.
- BEIS, 2018. Energy consumption in the UK (ECUK) Table 1.04 [WWW Document]. URL
   https://www.gov.uk/government/statistics/energy-consumption-in-the-uk (accessed
   4.1.19).
- Benini, L., Mancini, L., Sala, S., Schau, E., Manfredi, S., Pant, R., 2014. Normalisation
  method and data for Environmental Footprints, JRC Technical Reports. European
  Commission, Joint Research Center, Institute for Environment and Sustainability,
  Publications Office of the European Union, Luxemburg. https://doi.org/10.2788/16415
- Berrill, P., Arvesen, A., Scholz, Y., Gils, H.C., Hertwich, E.G., 2016. Environmental impacts
  of high penetration renewable energy scenarios for Europe. Environ. Res. Lett. 11.
  https://doi.org/10.1088/1748-9326/11/1/014012
- BIF REP, 2013. Building Insulation Foam Resource efficiencty action plan. [WWW
   Document]. URL www.wrap.org.uk/sites/files/wrap/BIF REAP v2.pdf
- BPD ltd., 2019a. Showersave QB1-21 Specification [WWW Document]. URL
   http://showersave.com/downloads/
- BPD ltd., 2019b. Downloads Showersave [WWW Document]. URL
   http://www.showersave.com/downloads/ (accessed 2.17.19).
- Bromley-Challenor, K., Kowalski, M., Barnard, R., Lynn, S., 2013. Water use in the UK food
  and drink industry. Technical report. Waste & Resources Action Programme (WRAP),
  Banbury, Oxon.
- Castro Molinare, J., 2014. Sustainability analysis of copper extraction and processing using
   LCA methods. Imperial College London.
- 616 CDA Inc., 2019. Melt Copper: Furnace types [WWW Document]. Copp. Dev. Assoc. Inc. 617 Copp. Alliance. URL https://www.copper.org/environment/sustainable-energy/electric618 motors/education/motor-rotor/production/proc09/process\_09\_94.html (accessed
  619 2.18.19).
- Chen, X., Su, Y., Reay, D., Riffat, S., 2016. Recent research developments in polymer heat
  exchangers A review. Renew. Sustain. Energy Rev. 60, 1367–1386.
  https://doi.org/10.1016/J.RSER.2016.03.024

- 623 Ciacci, L., Vassura, I., Passarini, F., 2017. Urban Mines of Copper: Size and Potential for 624 Recycling in the EU. Resources 6, 6. https://doi.org/10.3390/resources6010006
- 625 Clarke, J.A., Johnstone, C.M., Kelly, N.J., Strachan, P.A., Tuohy, P., 2008. The role of built
   626 environment energy efficiency in a sustainable UK energy economy. Energy Policy.
   627 https://doi.org/10.1016/j.enpol.2008.09.004
- 628 da Graça Carvalho, M., 2012. EU energy and climate change strategy. Energy 40, 19–22. 629 https://doi.org/10.1016/j.energy.2012.01.012
- Davis, J., He, J., Geyer, R., Sansom, M., Ley, J., Clift, R., Kwan, A., Jackson, T., 2006.
  Time-dependent material flow analysis of iron and steel in the UK. Resour. Conserv.
  Recycl. 51, 118–140. https://doi.org/10.1016/j.resconrec.2006.08.007
- 633 DEFRA, 2008. Future Water: The Government's water strategy for England. Norwich, UK.
- Dötsch, E., 2017. Use of thermochemical data in inductive melting. Dortmund, Germany.
- 635 Ecoinvent, 2018. Ecoinvent V3.5 Database. Zurich, Switzerland.
- Ekins, P., Lees, E., 2008. The impact of EU policies on energy use in and the evolution of
   the UK built environment. Energy Policy. https://doi.org/10.1016/j.enpol.2008.09.006
- Ekvall, T., Tillman, A.M., 1997. Open-loop recycling: Criteria for allocation procedures. Int. J.
   Life Cycle Assess. 2, 155–162. https://doi.org/10.1007/BF02978810
- 640 EST, 2013. At Home with Water. London.
- Fagan, J.E., Reuter, M.A., Langford, K.J., 2010. Dynamic performance metrics to assess
  sustainability and cost effectiveness of integrated urban water systems. Resour.
  Conserv. Recycl. 54, 719–736. https://doi.org/10.1016/J.RESCONREC.2009.12.002
- Franklin Associates, 2011. LIFE CYCLE INVENTORY FOR THE PRODUCTION AND USE
   OF INSTALLED RESIDENTIAL PIPING SYSTEMS FOR THREE HOUSE LAYOUTS.
   Plastic Piping Education Foundation.
- Gallagher, J., Basu, B., Browne, M., Kenna, A., McCormack, S., Pilla, F., Styles, D., 2019.
  Adapting Stand-Alone Renewable Energy Technologies for the Circular Economy
  through Eco-Design and Recycling. J. Ind. Ecol. 23, 133–140.
  https://doi.org/10.1111/jiec.12703
- 651 Geberit Sales Ltd, 2019. Geberit Mapress Stainless Steel system pipe: Product Data Sheet
  652 [WWW Document]. URL https://catalog.geberit.co.uk/en-GB/Geberit-Mapress653 Stainless-Steel-system-pipe,-CrNiMo,-small-bundle/OVE\_502637-39202.html
  654 (accessed 4.9.19).
- 655 Gerbens-Leenes, P.W., 2016. Energy for freshwater supply, use and disposal in the
  656 Netherlands: a case study of Dutch households. Int. J. Water Resour. Dev. 32, 398–
  657 411. https://doi.org/10.1080/07900627.2015.1127216
- 658 German Pipe, 2019. German Pipes copper pipes [WWW Document]. URL
   659 https://www.germanpipe.de/domains/germanpipe\_de/data/free\_docs/gp\_system\_e 660 komponenten\_kupfer\_edelstahl\_en.pdf
- Giurco, D., Petrie, J.G., 2007. Strategies for reducing the carbon footprint of copper: New
   technologies, more recycling or demand management? Miner. Eng. 20, 842–853.
   https://doi.org/10.1016/j.mineng.2007.04.014
- Glade, H., Moses, D., Orth, T., 2018. Polymer Composite Heat Exchangers, in: Bart, H.-J.,
  Scholl, S. (Eds.), Innovative Heat Exchangers. Springer International Publishing AG,
  pp. 53–116.

- Glöser, S., Soulier, M., Tercero Espinoza, L.A., 2013. Dynamic analysis of global copper
   flows. Global stocks, postconsumer material flows, recycling indicators, and uncertainty
   evaluation. Environ. Sci. Technol. 47, 6564–6572. https://doi.org/10.1021/es400069b
- Hussain, A.R.J., Alahyari, A.A., Eastman, S.A., Thibaud-Erkey, C., Johnston, S., Sobkowicz,
  M.J., 2017. Review of polymers for heat exchanger applications: Factors concerning
  thermal conductivity. Appl. Therm. Eng. 113, 1118–1127.
  https://doi.org/10.1016/J.APPLTHERMALENG.2016.11.041
- Ip, K., She, K., Adeyeye, K., 2018. Life-cycle impacts of shower water waste heat recovery:
  case study of an installation at a university sport facility in the UK. Environ. Sci. Pollut.
  Res. 25, 19247–19258. https://doi.org/10.1007/s11356-017-0409-0
- ISO, 2006. ISO 14040:2006 Environmental management -- Life cycle assessment -Principles and framework [WWW Document]. Int. Organ. Stand. URL
  https://www.iso.org/standard/37456.html (accessed 2.14.19).
- Johnson, J.X., McMillan, C., Keoleian, G.A., 2013. Evaluation of Life Cycle Assessment
   Recycling Allocation Methods. J. Ind. Ecol. 17. https://doi.org/10.1111/jiec.12050
- JRC-IES, E., 2011. ILCD handbook. Recommendations for Life Cycle Impact Assessment in
  the European context, International Reference Life Cycle Data System (ILCD)
  Handbook, Recommendations for life cycle impact assessment in the European
  context. European Commission Joint Research Centre Institute for Environment and
  Sustainability (EC JRC-IES) Publication Office of the European Union, Luxemburg.
  https://doi.org/10.2788/33030
- Livingston, T., 2018. Personal communication, Tony Livingston, 30th July 2018.
- Manouchehri, R., Banister, C.J., Collins, M.R., 2015. Impact of small tilt angles on the
   performance of falling film drain water heat recovery systems. Energy Build. 102, 181–
   186. https://doi.org/10.1016/J.ENBUILD.2015.05.024
- 692 McNabola, A., Shields, K., 2013. Efficient drain water heat recovery in horizontal domestic 693 shower drains. Energy Build. 59, 44–49. https://doi.org/10.1016/j.enbuild.2012.12.026
- Mudgal, S., Lyons, L., Bain, J., Dias, D., Faninger, T., Johansson, L., Dolley, P., Shields, L.,
   Bowyer, C., 2011. Plastic waste in the environment Final Report. European
   Commission (DG Environment).
- Nair, S., George, B., Malano, H.M., Arora, M., Nawarathna, B., 2014. Water–energy–
  greenhouse gas nexus of urban water systems: Review of concepts, state-of-art and
  methods. Resour. Conserv. Recycl. 89, 1–10.
  https://doi.org/10.1016/J.RESCONREC.2014.05.007
- Olson, D.W., Virta, R.L., Mahdavi, M., Sangine, E.S., Fortier, S.M., 2016. Natural graphite
  demand and supply Implications for electric vehicle battery requirements, in: Wessel,
  G.R., Greenberg, J.K. (Eds.), Geoscience for the Public Good and Global
- 704 Development : Toward a Sustainable Future. Geological Society of America, pp. 67–77.
- ONS, 2019. Population estimates for the UK, England and Wales, Scotland and Northern
   Ireland: mid-2018 [WWW Document]. Stat. Bull. Off. Natl. Stat. URL
   https://www.ons.gov.uk/peoplepopulationandcommunity/populationandmigration/popula
   tionestimates/bulletins/annualmidyearpopulationestimates/mid2018 (accessed 4.23.20).
- Pipelife UK, 2019. Qual-Pex Barrier Pipe Specification [WWW Document]. URL
  https://www.pipelife.co.uk/uk/product\_overview/Qual-Pex\_Barrier\_Pipe.php (accessed
  4.9.19).
- 712 PRé Sustainability, 2018. SimaPro 9.0. 3818 LE Amersfoort, The Netherlands.

- Prek, M., 2004. Environmental impact and life cycle assessment of heating and air
  conditioning systems, a simplified case study. Energy Build. 36, 1021–1027.
  https://doi.org/10.1016/J.ENBUILD.2004.06.008
- Q-Blue b.v., 2019. Q-Blue Showersave [WWW Document]. URL https://www.q blue.nl/en/products/q-blue-showersave-en (accessed 2.13.19).
- Q-Blue b.v., 2018. Installation Manual Showersave QB1-12-16-21 [WWW Document].
   https://doi.org/http://dx.doi.org/10.1016/j.metabol.2013.01.021
- RenewABILITY Energy Inc., 2019. RenewABILITY Energy Inc. Home of the Power-Pipe
   Drain Water Heat Recovery System [WWW Document]. URL http://renewability.com/
   (accessed 2.13.19).
- Rosenow, J., 2012. Energy savings obligations in the UK-A history of change. Energy Policy.
   https://doi.org/10.1016/j.enpol.2012.06.052
- Ruhrberg, M., 2006. Assessing the recycling efficiency of copper from end-of-life products in
   Western Europe. Resour. Conserv. Recycl. 48, 141–165.
   https://doi.org/10.1016/j.resconrec.2006.01.003
- Sanders, K.T., Webber, M.E., 2012. Evaluating the energy consumed for water use in the
  United States. Environ. Res. Lett. 7, 034034. https://doi.org/10.1088/17489326/7/3/034034
- Schuitema, R., Sijpheer, N.C., Bakker, E.J., 2005. Energy performance of a drainwater heat
   recovery system. Experimental results of drainwater heat recovery in ECN research
   dwellings, in: CISBAT Conference. Lausanne, Switzerland, p. 7.
- Siddiqi, A., Fletcher, S., 2015. Energy Intensity of Water End-Uses. Curr. Sustain. Energy
   Reports 2, 25–31. https://doi.org/10.1007/s40518-014-0024-3
- Słyś, D., Kordana, S., 2014. Financial analysis of the implementation of a Drain Water Heat
  Recovery unit in residential housing. Energy Build. 71, 1–11.
  https://doi.org/10.1016/J.ENBUILD.2013.11.088
- Spriet, J., McNabola, A., 2019a. Decentralized drain water heat recovery from commercial
   kitchens in the hospitality sector. Energy Build. 194, 247–259.
- Spriet, J., McNabola, A., 2019b. Drain Water Heat Recovery in Commercial Kitchens: Case
  of Tourist Attraction, 14th Conference on Sustainable Development of Energy, Water
  and Environment Systems (SDEWES). https://www.dwr-uisce.eu/conferenceproceedings-and-posters, Dubrovnik.
- Technoform, 2014. FULL POLYMER HEAT-EXCHANGER TUBES. Technoform
   Kunststoffprofile GmbH, Otto-Hahn-Str 34, 34253 Lohfelden, Germany.
- Tikana, L., Sievers, H., Klassert, A., 2005. Life Cycle Assessment of Copper Products.
   Düsseldorf, Germany. https://doi.org/10.1007/BF02979447
- van der Hoek, J., 2011. Energy from the water cycle: a promising combination to operateclimate neutral. Water Pract. Technol. 6.
- Wong, L.T., Mui, K.W., Guan, Y., 2010. Shower water heat recovery in high-rise residential
  buildings of Hong Kong. Appl. Energy 87, 703–709.
  https://doi.org/10.1016/J.APENERGY.2009.08.008

754

#### 755 Figure and Table Captions:

Figure 1: System boundaries of the LCAs on the heat recovery system (left, shown for the copper system) and
 extended boundaries for evaluating the savings potential through the replacement of heat energy sources.

Figure 2: Environmental burdens arising from the life cycle of drain water heat recovery systems consisting of inline heat exchanger, 10 m pipework, fittings and insulations. Percentage in brackets stands for the share of
recycled copper. PE: polyethylene, PP-GR: Polypropylene-Graphite. GWP: Global Warming Potential; HTP:
Human Toxicity Potential; POFP: Photochemical Ozone Formation Potential; AP: Acidification Potential; FEP:
Freshwater Eutrophication Potential; FEToxP: Freshwater Ecotoxicity Potential; RDP: Mineral, fossil & renewable
Resource Depletion Potential. All scenarios as described in Table 1.

Figure 3: LCA of heat recovery systems (scenarios 2 and 5): Relative contribution of the life cycle stages to the environmental impacts of the two heat recovery systems including 10 m pipework. Left: scenario 2: copper system with 35% recycled copper input. Right: scenario 5: PP-GR composite system with PP-GR heat exchanger and pipework from PE. GWP: Global Warming Potential; HTP: Human Toxicity Potential; POFP: Photochemical Ozone Formation Potential; AP: Acidification Potential; FEP: Freshwater Eutrophication Potential; FEToxP: Freshwater Ecotoxicity Potential; RDP: Mineral, fossil & renewable Resource Depletion Potential; Hex: Heat exchanger; EoL: End of Life.

Figure 4: Comparison of LCA results for the heat exchanger and pipework for (clockwise from top left): global
warming potential (GWP), resource depletion potential (RDP), freshwater ecotoxicity potential (FEtoxP) and
human toxicity potential (HTP). Left two bars: complete life cycle of a heat exchanger system without pipework.
Right three bars: life cycle of pipework from polyethylene (PE), steel and copper (35% recycled content).

775 Figure 5: Environmental impacts per kWh for water heating. Comparison of heat recovery from drain water with 776 other renewable and non-renewable heat sources, including the current UK energy mix for water heating ("mix"). 777 Burdens of the heat recovery system as in scenario 4 with two different water flow-rates found in UK commercial 778 food outlets. H recov. Low: low impact case due to higher flow-rate of 12,500 L/day. H recov. High: high impact 779 case due to lower flowrate of 360 L/day. NG: natural gas, electricity: UK grid mix, wood: wood biomass 780 combustion, geo: geothermal, solar: solar thermal. GWP: Global Warming Potential; HTP: Human Toxicity 781 Potential; POFP: Photochemical Ozone Formation Potential; AP: Acidification Potential; FEP: Freshwater 782 Eutrophication Potential; FEToxP: Freshwater Ecotoxicity Potential; RDP: Mineral, fossil & renewable Resource

783 Depletion Potential

Figure 6: Normalised net environmental savings (positive values) through heat recovery from a commercial kitchen
after 10 years depending on the yearly water consumption. GWP: Global Warming Potential; HTP: Human Toxicity
Potential; POFP: Photochemical Ozone Formation Potential; AP: Acidification Potential; FEP: Freshwater
Eutrophication Potential; FEToxP: Freshwater Ecotoxicity Potential; RDP: Mineral, fossil & renewable Resource
Depletion Potential.

789 Table 1: Overview of assumptions for scenarios of the LCAs.

Table 2: Types of energy and respective database modules used for determination of environmental savings
 through heat recovery

Table 3: Environmental payback times in years for the heat recovery system of the Penrhyn Castle case study.
Comparison of the copper (35% recycled content) and the PP-GR systems including 10 m of pipework with different
energy sources for water heating. Bold and italic: Impacts are not paid back within a 10-year lifetime. NG = natural
gas. Mix: Current UK Energy mix for heating water in the service sector (BEIS, 2018). GWP: Global Warming
Potential; HTP: Human Toxicity Potential; POFP: Photochemical Ozone Formation Potential; AP: Acidification
Potential; FEP: Freshwater Eutrophication Potential; FEToxP: Freshwater Ecotoxicity Potential; RDP: Mineral,
fossil & renewable Resource Depletion Potential. Energy sources as in Table 2.

Table 4: Yearly net environmental savings potential for the UK through heat recovery from wastewater in all
 commercial food outlets. eq = equivalent